

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

**DISTRICT I**  
P. O. Box 1980, Hobbs, NM 88240

**DISTRICT II**  
P. O. Drawer DD, Artesia, NM 88210

**DISTRICT III**  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**

P. O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-30657
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-2229
7. Lease Name or Unit Agreement Name Philmex
8. Well No. 37
9. Pool name or Wildcat Maljamar Grayburg/SA

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK  
TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER
2. Name of Operator Phillips Petroleum Company
3. Address of Operator 4001 Penbrook Street, Odessa, Texas 79762
4. Well Location Unit Letter <u>K</u> : <u>1980</u> Feet From The <u>south</u> Line and <u>1880</u> Feet From The <u>west</u> Line Section <u>26</u> Township <u>17-S</u> Range <u>33-E</u> NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) <u>4134.5</u> GR unprepared

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-08-89: Spud 12-1/4" hole at 10:30 a.m. MST.  
10-09-89: TD'd 12-1/4" hole at 9:00 p.m. Set 8-5/8" 24# J-55 ST&C casing at 1500' w/1000 sx Class "C", 2% CaCl. Circ 185 sx cmt. WOC 13½ hrs Tested BOP and csg to 2000 psi.  
10-15-89: Td'd 7-7/8" hole at 11:55 p.m. at 4800'. Schlumberger ran DLL-GR-Cal from TD to 2500'; LDT-GR-Cal from TD to 2500' and CNL-GR-Cal from 2500 to surface.

SEE REVERSE SIDE

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. M. Sanders  
TYPE OR PRINT NAME L. M. Sanders

TITLE Regulation & Proration DATE 10-17-89  
Supervisor  
TELEPHONE NO. 915/367-1488

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT I SUPERVISOR

TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

**OCT 19 1989**

**RECEIVED**

**OCT 18 1989**

**OCD  
HOBBS OFFICE**

Waiting on completion unit.

4:00 a.m. 10-17-89.

Set 5-1/2" 15.5# J-55 LT&C casing at 4800' with 900 sx Howco Lite  
w/5% salt + 300 sx "C" 50/50 Poz 3% salt, 10# Microbond & 4/10% Halad 322.  
Displaced with 10 bbls 10% acetic acid and 103 1/2 bbls 2% KCL FW. Circ  
265 sx cmt. NU BOP and set 5-1/2" casing slips. Released rig at