

Submit to:
District Office

DISTRICT I
P.O. Box 1980, El Paso, NM 88520

DISTRICT II
P.O. Drawer DD, Alamogordo, NM 88210

DISTRICT III
1000 Rio Pecos Parkway, El Paso, NM 88410

El Paso County
Oil & Gas Division
P.O. Box 2038
El Paso, Texas 79901-2038
87504-2038

Form 103
10-11-89

GENERAL NOTICES AND REMARKS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☐ GAS WELL ☐ CO2 inj. ☒	WELL DATA 30-025-30065 5. Indicate Type of Well ☐ FEE ☐ 6. State Oil & Gas E-2229
2. Name of Operator Phillips Petroleum Company	7. Lease Name or Unit Name Philmex
3. Address of Operator 4001 Penbrook Street, Odessa, Texas 79762	8. Well No. 38
4. Well Location Unit Lease M : 1307 Feet From The North Line 1245 Feet From The West Line Section 28 Township 17-S Range 33-E El Paso County	9. Pool Name or Well Unit Maljamar Graywarp-SA
10. Existing Well Depth (LTD, R, H, GR, etc.) 4132.5' (unprepared)	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-23-89: Spud 12-1/4" hole @ 8:30 a.m.

9-24-89: Td'd 12-1/4" hole @ 3:30 p.m. Set 8-5/8" 24# J-55 ST&C csg @ 1455' w/ 1000 sx Class "C", 2% CaCl. Circ. 212 sx cmt. Total WOC time 16-1/2 hrs. Tst'd BOP and csg to 2000 psi, held OK.

9-25 thru

9-28-89: Drld to 4190', POOH. WIH w/core bbl.

9-29 thru

10-05-89: Core #1 from 4190'-4251', Core #2 from 4251'-4311'; Core #3 from 4311' to 4374', Core #4 from 4374'-4436', Core #5 from 4436'-4497'; Core #6 from 4497' to 4558'; Core #7 from 4558'-4620'; Core #8 from 4620'-4682'. Drld hole to 4800' Td'd @ 5:30 p.m. on October 5.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SEE REVERSE SIDE

SIGNATURE

L.M. Sanders

TITLE

Reg. & Pro. Supervisor

DATE

10/11/89

TYPE OR PRINT NAME

L. M. Sanders

TELEPHONE NO. 367-1488

(This space for Stamp Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

OCT 13 1989

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

10-10-89: Schlumberger ran LDT-CNL-GR-Cal from 4800'-2500', turned off LDT @ 2500', continued w/CNL-GR-Cal to surface, CAL quit @ 2300'. Ran EPT from 4800'-4100', pulsed Neutron from 4800'-4100' and DLL from 4800'-2500'. Loggers TD @ 4304'. Set 5-1/2" 15.5# J 55 LT&C csg @ 4800' w/1125 sx Hovco Lite + 5% salt tailed w/200 sx Class "C" 50/50 Poz w/no gel + 3% salt + 10#/sx Microbond + 4% Halad 322. Circ. 325 sx cmt. ND BOP. set csg slips, cut off 5-1/2" csg. Released rig @ 11:00 a.m., 10-07-89. Waiting on completion unit.