

TRANSMITTED FROM 505 8 9264
(JULY 1989)
(Formerly 9-331)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

04.06.90 1 13
OF COPIES REQUIRED
(Other instructions on re-
verse side)

P.02 *Carlsbad RA
Form No.
M060-3160-4

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	2. NAME OF OPERATOR Woodbine Petroleum, Inc.	3a. Area Code & Phone No. (214) 855-6263	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1650 FWL and 2310' FSL	5. LEASE DESIGNATION AND SERIAL NO. NM - 0175744 0175774	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	7. UNIT AGREEMENT NAME	8. FARM OR LEASE NAME Mobil - Federal #	9. WELL NO. #4	10. FIELD AND POOL, OR WILDCAT West Lusk Delaware	11. SEC., T., R., M., OR BLK. AND SURVEY OR ARMA 21 T19S R32E	12. COUNTY OR PARISH Lea	13. STATE TX
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, OR, etc.) 3585' GL	16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data										

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
ABANDON OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETION
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
ABANDON OR ACIDIZING
(Other) Set production casing

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

7. BEST KID PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all major sand zones perti-
nent to this work.)

* revision of sundry notice sent 4/24/90

3/13/90 Drilled out cement and casing shoe.

3/13-30/90 Drilled from 477' to 7230' with a 7 7/8" bit.

3/30/90 Ran 5 1/2", 15.5 #/ft, J-55 casing w/ DV tool at 2860' KB. Cemented with 530 sxs of Howco lite w/ 15# salt/sx, followed by 800 sxs of 50/50 POS w/ 5# salt/sx. Dropped bomb to open DV tool. Circulated 4 hrs. Cemented thru DV tool with 1100 sx Howco lite, 15 #salt/sx & 300 sx 50/50 POS, 5 # salt/sx.

3/31/90 Wait on cement. Ran temp survey. Found top of cement at 1250'. Ran 1" tubing to 1336'. Cemented with 720 sx cement to circulate.
(A representative of the BLM was on location.)

ACCEPTED FOR RECORD

MAY 24 1990

I hereby certify that the foregoing is true and correct

SIGNED Ben Nivens TITLE Petroleum Engineer

CARLSBAD, NEW MEXICO

DATE 4/24/90

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the