

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-30799
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 857948
7. Lease Name or Unit Agreement Name VACUUM GRAYBURG SAN ANDRES UNIT
8. Well No. 148
9. Pool name or Wildcat VACUUM GRAYBURG SAN ANDRES
10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR-3997', KB-4010'

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator TEXACO PRODUCING INC.
3. Address of Operator P. O. Box 3109 Midland, Texas 79702	4. Well Location Unit Letter D : 1330 Feet From The NORTH Line and 660 Feet From The WEST Line Section 1 Township 18-SOUTH Range 34-EAST NMPM LEA County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR-3997', KB-4010'	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. TD 8 3/4 HOLE @ 5000' AT 3:30am 5-20-90.
2. ATLAS RAN GR-DLL-MSFL & GR-CNL-ZDL-CAL FROM 5000' TO 2800'. GR TO SURFACE.
3. RAN 123 JTS OF 7, 26#, J-55, LT&C CSG. SET AT 5000'. WESTERN CEMENTED w/ 800 SX 35/65 POZ CLASS H w/ 6% GEL, 5% SALT & 1/4# FLOCELE @ 12.8ppg. F/B 250 SX CLASS H @ 15.6ppg. CIRC 120 SX. JOB COMPLETE AT 1:00pm 5-21-90.
4. INSTALL WELLHEAD. FMC TEST TO 2000#.
5. RELEASE RIG AT 6:00pm 5-21-90.
6. PREP TO COMPLETE.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE C. P. Basham TITLE DRILLING SUPERINTENDENT DATE 05-23-90  
TYPE OR PRINT NAME C. P. BASHAM TELEPHONE NO. 915-6884620

(This space for State Use)  
ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT I SUPERVISOR

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

MAY 29 1990