(July 1989)

BLM Roswell District CONTACT RECEIVING OFFICE FOR NUMBER Modified Form No. Form 3160-5 UNITED STATES NM060-3160-4 OF COPIES REQUIRED (Other instructions on reverse DEPARTMENT OF THE INTERIOR 5. LEASE DESIGNATION AND SERIAL NO. (Formerly 9-331) BUREAU OF LAND MANAGEMENT LC-069420 IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals.) 7. UNIT AGREEMENT NAME WELL X GAS WELL OTHER 8. FARM OR LEASE NAME NAME OF OPERATOR West Corbin Federal Southland Royalty Company 3a. AREA CODE & PHONE NO. WELL NO. ADDRESS OF OPERATOR 21 Desta Dr., Midland, TX 79705 915/686-5600 10, FIEED AND POOL OR WILDCAT LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) West Cerbin (Bone Spring) At surface 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 660' FNL & 330' FWL. Sec. 07, T18S, R33E Sec. 07, T18S, R33E 12. COUNTY OR PARISH 13. STATE 14 PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) NM 3918' GR. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data 16 SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: WATER SHUT-OFF REPAIRING WELL PULL OR ALTER CASING TEST WATER SHUT-OFF ALTERING CASING MULTIPLE COMPLETE ERACTURE TREATMENT FRACTURE TREAT SHOOTING OR ACIDIZING ABANDONMENT* ABANDON* SHOOT OR ACIDIZE Х CHANGE PLANS (Other) REPAIR WELL (NOTE: Report results of multiple completion on Well (Other) Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this HOLE/CASING PROGRAM: Drill 12 1/4" hole to 1500'. Set 8 5/8" csg @1500' and cmt to surface w/600 sx Cl. C + 4% Gel + 2% Calcium Chloride lead and 200 sx Cl. C + 2% Calcium Chloride tail. Drill 7 7/8" hole to 8900'. Set5 1/2" csq @ 8900' with a stage collar @5000'. Cmt to surface. 1st Stage: 500 sx 12.5 ppg Silicalite & 30 sx Cl H tail. 2nd Stage: 600 sx Cl. C lite + 12% salt & 200 sx Cl. C Neat tail. MUD PROGRAM: 0-1500' = FW Spud Mud; 1500'-8000' = Saturated Brine; 8000'-TD = Saturated Brine/ Polymer/Starch/ BOP PROGRAM: 11"-3M BOP to be installed on 8 5/8" and left on for remainder of drilling. Stack to consist of annular BOP, blind ram BOP, and one pipe ram BOP. Test BOP's @8 5/8" nipple-up using an independent teser. 5 1/2", 17#/ft, K-55, STC CASING DETAIL: 8 5/8", 24#/ft, K-55, STC

8. I hereby certify that the foregoing is true and correct SIGNED ROUTER TITLE	Sr. Staff Env./Reg. Spec.	DATE	2/15/90
(This space for Federal or State office use)	建 理生产会 (1936年1967)		
APPROVED BY		DATE	2 de 90

HOBBS GENCE OCD

LEB 5 I 1880

BECEINED