arm 3160-5	UNIT	TED STATES	Bulger Burger No. 1004-0135		
une (990)	DEPARTMEN	T OF THE INTERIOR	Expires: March 31, 1993		
	BUREAU OF L	5. Lease Designation and Scrist No.			
			NM-59392		
		AND REPORTS ON WELLS	5. If Indian, Allottee or Tribe Name		
Uo not use this for Ut	a "APPLICATION FOR	li or to deepen or reentry to a different reservol 3 PERMIT—'' for such proposals			
	7. If Unit or CA, Agreement Designation				
1. Type of Well	–	8. Well Name and No.			
Cil Gas Well X Well 2. Name of Operator	L] Caher	Lusk AHB Federal #1			
•	EUM CORPORATION	(505) 748-1471)	9. API Well No.		
IAIES PEIROL 3. Address and Telephone N			30-025-30808		
• • • • • • • • •	h St., Artesia, M	M 88210	10. Field and Pool, or Exploratory Area		
4 Location of Well (Foqua	e, Sec., T., R., M., or Survey De	escription)	Undesignated Delaware		
-		on 35-T19S-R32E (Unit B, NWNE)	11. County or Parish, State		
			Lea Co., NM		
2. CHECK	APPROPRIATE BOX	a) TO INDICATE NATURE OF NOTICE, REP	ORT, OR OTHER DATA		
	SUBMISSION	TYPE OF ACTIO			
Notice a	F Intent	Abandopmeni	Change of Plane		
	I ENOCIAL	Recompletion	New Construction		
X Subseque	ent Report	Plugging Back	Nos-Baulias Procuring		
		Casing Repair	Witter Shul-Off		
Pinal Al	bandonment Notice	Altering Capità	Conversion to Injection		
		X Ouer Perforate & acidize			
			(Hour: Report results of multiple complexion on Well Complexion or Recomplexion Report and Log form)		
13. Describe Promoted or Co	exploied Operations (Clearly sime a	Il pertheest details, and give pertinent dates, including estimated date of su	ming any proposed work. If well is directionally drilled,		
man tabaseface loca	uions and measured and the venix	cal deputs for all markers and sours pressures to this work.)* TTH with 4" casing guns and perfo	rated 6162-6316' w/40 .42"		
give subsurface loce 8-30-96 - Ri	geed up wireline.	. TIH with 4" casing guns and perfo	rated 6162-6316' w/40 .42" , and 6306-6316' (1 SPF -		
yrr ubwrlee lee 8-30-96 - Ri holes as fol Delaware)	gged up wireline. lows: 6162-6174 ¹ TOOH with casing	. TIH with 4" casing guns and perfo , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIM	',and 6306-6316' (1 SPF - l with RBP, packer and		
yrre ubburface leca 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin	gged up wireline. lows: 6162-6174 ¹ TOOH with casing	. TIH with 4" casing guns and perfo , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIN 570' and tested to 1500 psi. Set pa	' and 6306-6316' (1 SPF - l with RBP, packer and icker at 6233'. Acidized		
yrr wbwrface leca 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin	gged up wireline. lows: 6162-6174 ¹ TOOH with casing	. TIH with 4" casing guns and perfo , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIN 570' and tested to 1500 psi. Set pa	' and 6306-6316' (1 SPF - l with RBP, packer and icker at 6233'. Acidized		
yrre unburface loca 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin perforations Swabbing.	gged up wireline. lows: 6162-6174' TOOH with casing ng. Set RBP at 64 6260-6316' with	. TIH with 4" casing guns and perford , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIN 420' and tested to 1500 psi. Set pa 2000 gallons 7-1/27 iron control ac	',and 6306-6316' (1 SPF - l with RBP, packer and icker at 6233'. Acidized id and ball sealers.		
<pre>give ubburface leas 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin perforations Swabbing. 8-31-96 - Re</pre>	gged up wireline. lows: 6162-6174' TOOH with casing ng. Set RBP at 64 6260-6316' with	. TIH with 4" casing guns and perfor , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIN 420' and tested to 1500 psi. Set pa 2000 gallons 7-1/27 iron control ac TIH and circulated off RBP. Unset F	",and 6306-6316' (1 SPF - l with RBP, packer and icker at 6233'. Acidized id and ball sealers. RBP. Pulled up and reset		
yrre unburface here 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin perforations Swabbing. 8-31-96 - Re RBP at 6240'	gged up wireline. lows: 6162-6174' TOOH with casing ug. Set RBP at 64 6260-6316' with eleased packer.	. TIH with 4" casing guns and perfor , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIN 420' and tested to 1500 psi. Set pa 2000 gallons 7-1/27 iron control ac TIH and circulated off RBP. Unset F 1500 psi. Pulled up and set packer	" and 6306-6316' (1 SPF - l with RBP, packer and toker at 6233'. Acidized tid and ball sealers. RBP. Pulled up and reset that 6102'. Acidized		
yrr ubbriact laca 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin perforations Swabbing. 8-31-96 - Re RBP at 6240' perforations	gged up wireline. lows: 6162-6174' TOOH with casing ng. Set RBP at 64 6260-6316' with eleased packer. . Tested RBP to 6162-6173' with	. TIH with 4" casing guns and perfor , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIN 420' and tested to 1500 psi. Set pa 2000 gallons 7-1/2% iron control ac TIH and circulated off RBP. Unset F 1500 psi. Pulled up and set packer 1500 gallons 7-1/2% NEFE acid and b	" and 6306-6316' (1 SPF - l with RBP, packer and toker at 6233'. Acidized tid and ball sealers. RBP. Pulled up and reset that 6102'. Acidized		
<pre>unc uburface leas 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin perforations Swabbing. 8-31-96 - Re RBP at 6240' perforations 9-1-3-96 - S</pre>	gged up wireline. lows: 6162-6174' TOOH with casing ag. Set RBP at 64 6260-6316' with eleased packer. . Tested RBP to 6162-6173' with Symbol. Shut we	. TIH with 4" casing guns and perfor , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIH 420' and tested to 1500 psi. Set pa 2000 gallons 7-1/2% iron control ac TIH and circulated off RBP. Unset F 1500 psi. Pulled up and set packer 1500 gallons 7-1/2% NEFE acid and b 11 in.	" and 6306-6316" (1 SPF - l with RBP, packer and icker at 6233". Acidized id and ball sealers. RBP. Pulled up and reset at 6102". Acidized ball sealers. Swabbing.		
yrr ubburface lease 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin perforations Swabbing. 8-31-96 - Re RBP at 6240' perforations 9-1-3-96 - Se 9-1-3-96 - Se	gged up wireline. lows: 6162-6174' TOOH with casing ag. Set RBP at 64 6260-6316' with eleased packer. . Tested RBP to 6162-6173' with Swabbed. Shut well eased packer and	. TIH with 4" casing guns and perfor , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIH 420' and tested to 1500 psi. Set pa 2000 gallons 7-1/2% iron control ac TIH and circulated off RBP. Unset F 1500 psi. Pulled up and set packer 1500 gallons 7-1/2% NEFE acid and b 11 in. washed balls off RBP. Moved and set	 P. and 6306-6316' (1 SPF - l with RBP, packer and licker at 6233'. Acidized Cardina ball sealers. CBP. Pulled up and reset Cat 6102'. Acidized Call sealers. Swabbing. Cat RBP at 5277'. Tested RBF 		
yre ubwriaet leas 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin perforations Swabbing. 8-31-96 - Re RBP at 6240' perforations 9-1-3-96 - Se 9-4-96 - Rel to 1500 psic	gged up wireline. lows: 6162-6174' TOOH with casing ag. Set RBP at 64 6260-6316' with eleased packer. 7 . Tested RBP to 6162-6173' with Swabbed. Shut well leased packer and TOOH with packs	. TIH with 4" casing guns and perfor , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIN 420' and tested to 1500 psi. Set pa 2000 gallons 7-1/2% iron control ac TIH and circulated off RBP. Unset F 1500 psi. Pulled up and set packer 1500 gallons 7-1/2% NEFE acid and b 11 in. washed balls off RBP. Moved and set part of the set of the	 P. and 6306-6316' (1 SPF - l with RBP, packer and licker at 6233'. Acidized and ball sealers. RBP. Pulled up and reset at 6102'. Acidized ball sealers. Swabbing. RBP at 5277'. Tested RBF TIH with 4" casing guns 		
give ubbufface lease 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin perforations Swabbing. 8-31-96 - Re RBP at 6240' perforations 9-1-3-96 - S 9-4-96 - Rel to 1500 psi. and perforat	gged up wireline. lows: 6162-6174' TOOH with casing g. Set RBP at 64 6260-6316' with eleased packer. . Tested RBP to 6162-6173' with wabbed. Shut well leased packer and TOOH with packet red 5042-5114' w/	. TIH with 4" casing guns and perfor , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIH 420' and tested to 1500 psi. Set pa 2000 gallons 7-1/27 iron control ac FIH and circulated off RBP. Unset F 1500 psi. Pulled up and set packer 1500 gallons 7-1/27 NEFE acid and b 11 in. washed balls off RBP. Moved and set er and tubing. Rigged up wireline. 10 .42" holes as follows: 5042, 53.	 P. and 6306-6316' (1 SPF - l with RBP, packer and licker at 6233'. Acidized and ball sealers. RBP. Pulled up and reset at 6102'. Acidized ball sealers. Swabbing. RBP at 5277'. Tested RBF TIH with 4" casing guns 54, 84, 88, 96, 5102, 06, 		
give ubbufface lease 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin perforations Swabbing. 8-31-96 - Re RBP at 6240' perforations 9-1-3-96 - S 9-4-96 - Rel to 1500 psi. and perforat	gged up wireline. lows: 6162-6174' TOOH with casing g. Set RBP at 64 6260-6316' with eleased packer. Tested RBP to 6162-6173' with wabbed. Shut well leased packer and TOOH with packet to 5042-5114' w/2 TOOH with 4" of	. TIH with 4" casing guns and perfor , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIH 420' and tested to 1500 psi. Set pa 2000 gallons 7-1/27 iron control ac FIH and circulated off RBP. Unset F 1500 psi. Pulled up and set packer 1500 gallons 7-1/27 NEFE acid and b 11 in. washed balls off RBP. Moved and set er and tubing. Rigged up wireline. 10 .42" holes as follows: 5042, 53, casing guns and rigged down wireline.	 P. and 6306-6316' (1 SPF - l with RBP, packer and licker at 6233'. Acidized and ball sealers. RBP. Pulled up and reset at 6102'. Acidized ball sealers. Swabbing. RBP at 5277'. Tested RBF TIH with 4" casing guns 54, 84, 88, 96, 5102, 06, and the sealer and 		
yere subserface lease 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin perforations Swabbing. 8-31-96 - Re RBP at 6240' perforations 9-1-3-96 - S 9-4-96 - Rel to 1500 psi. and perforat 10 and 5114' tubing. Set	gged up wireline. lows: 6162-6174' TOOH with casing g. Set RBP at 64 6260-6316' with eleased packer. 7 . Tested RBP to 6162-6173' with Swabbed. Shut well leased packer and TOOH with pack ted 5042-5114' w/ . TOOH with 4" of packer at 4977'	. TIH with 4" casing guns and perfor , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIH 420' and tested to 1500 psi. Set pa 2000 gallons 7-1/27 iron control ac TIH and circulated off RBP. Unset F 1500 psi. Pulled up and set packer 1500 gallons 7-1/27 NEFE acid and b 11 in. washed balls off RBP. Moved and set er and tubing. Rigged up wireline. 10 .42" holes as follows: 5042, 53, casing guns and rigged down wireline. Acidized perforations 5042-5114'	 P. and 6306-6316' (1 SPF - l with RBP, packer and licker at 6233'. Acidized and ball sealers. RBP. Pulled up and reset at 6102'. Acidized ball sealers. Swabbing. RBP at 5277'. Tested RBF TIH with 4" casing guns 54, 84, 88, 96, 5102, 06, and the sealer and 		
give tuburface lease 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin perforations Swabbing. 8-31-96 - Re RBP at 6240' perforations 9-1-3-96 - S 9-4-96 - Rel to 1500 psi. and perforat 10 and 5114' tubing. Set	gged up wireline. lows: 6162-6174' TOOH with casing g. Set RBP at 64 6260-6316' with eleased packer. 7 . Tested RBP to 6162-6173' with Swabbed. Shut well leased packer and TOOH with pack ted 5042-5114' w/ . TOOH with 4" of packer at 4977'	. TIH with 4" casing guns and perfor , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIH 420' and tested to 1500 psi. Set pa 2000 gallons 7-1/27 iron control ac FIH and circulated off RBP. Unset F 1500 psi. Pulled up and set packer 1500 gallons 7-1/27 NEFE acid and b 11 in. washed balls off RBP. Moved and set er and tubing. Rigged up wireline. 10 .42" holes as follows: 5042, 53, casing guns and rigged down wireline.	 P. and 6306-6316' (1 SPF - l with RBP, packer and licker at 6233'. Acidized and ball sealers. RBP. Pulled up and reset at 6102'. Acidized ball sealers. Swabbing. RBP at 5277'. Tested RBF TIH with 4" casing guns 54, 84, 88, 96, 5102, 06, and the sealer and 		
give tuburface lease 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin perforations Swabbing. 8-31-96 - Re RBP at 6240' perforations 9-1-3-96 - S 9-4-96 - Rel to 1500 psi. and perforat 10 and 5114' tubing. Set	gged up wireline. lows: 6162-6174' TOOH with casing g. Set RBP at 64 6260-6316' with eleased packer. 7 . Tested RBP to 6162-6173' with Swabbed. Shut well leased packer and TOOH with pack ted 5042-5114' w/ . TOOH with 4" of packer at 4977'	. TIH with 4" casing guns and perfor , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIH 420' and tested to 1500 psi. Set pa 2000 gallons 7-1/27 iron control ac TIH and circulated off RBP. Unset F 1500 psi. Pulled up and set packer 1500 gallons 7-1/27 NEFE acid and b 11 in. washed balls off RBP. Moved and set er and tubing. Rigged up wireline. 10 .42" holes as follows: 5042, 53, casing guns and rigged down wireline. Acidized perforations 5042-5114'	 P. and 6306-6316' (1 SPF - l with RBP, packer and licker at 6233'. Acidized and ball sealers. RBP. Pulled up and reset at 6102'. Acidized ball sealers. Swabbing. RBP at 5277'. Tested RBF TIH with 4" casing guns 54, 84, 88, 96, 5102, 06, and the sealer and 		
prot subsurface here 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin perforations Swabbing. 8-31-96 - Re RBP at 6240' perforations 9-1-3-96 - S 9-4-96 - Rel to 1500 psi. and perforat 10 and 5114' tubing. Set iron control	gged up wireline. lows: 6162-6174' TOOH with casing g. Set RBP at 64 6260-6316' with eleased packer. 7 . Tested RBP to 6162-6173' with Swabbed. Shut well eased packer and TOOH with pack ted 5042-5114' w/ . TOOH with 4" of packer at 4977' HCL acid. Swabl	. TIH with 4" casing guns and perfor , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIH 420' and tested to 1500 psi. Set pa 2000 gallons 7-1/27 iron control ac TIH and circulated off RBP. Unset F 1500 psi. Pulled up and set packer 1500 gallons 7-1/27 NEFE acid and b 11 in. washed balls off RBP. Moved and set er and tubing. Rigged up wireline. 10 .42" holes as follows: 5042, 53, casing guns and rigged down wireline. Acidized perforations 5042-5114'	 P. and 6306-6316' (1 SPF - l with RBP, packer and acker at 6233'. Acidized and ball sealers. RBP. Pulled up and reset at 6102'. Acidized ball sealers. Swabbing. RBP at 5277'. Tested RBF TIH with 4" casing guns 54, 84, 88, 96, 5102, 06, and the sealer and 		
prot subsurface here 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin perforations Swabbing. 8-31-96 - Re RBP at 6240' perforations 9-1-3-96 - S 9-4-96 - Rel to 1500 psi. and perforat 10 and 5114' tubing. Set iron control	gged up wireline. lows: 6162-6174' TOOH with casing g. Set RBP at 64 6260-6316' with eleased packer. 7 . Tested RBP to 6162-6173' with Swabbed. Shut well leased packer and TOOH with pack ted 5042-5114' w/ . TOOH with 4" of packer at 4977'	TIH with 4" casing guns and perford , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIH 420' and tested to 1500 psi. Set para 2000 gallons 7-1/27 iron control ac TIH and circulated off RBP. Unset F 1500 psi. Pulled up and set packer 1500 gallons 7-1/27 NEFE acid and b 11 in. washed balls off RBP. Moved and set er and tubing. Rigged up wireline. 10 .42" holes as follows: 5042, 53, casing guns and rigged down wireling. Acidized perforations 5042-5114' bed. Shut well in.	 and 6306-6316' (1 SPF - l with RBP, packer and acker at 6233'. Acidized and ball sealers. RBP. Pulled up and reset at 6102'. Acidized ball sealers. Swabbing. RBP at 5277'. Tested RBF TIH with 4" casing guns 54, 84, 88, 96, 5102, 06, and with 1500 gallons 7-1/2X 		
une suburface here 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin perforations Swabbing. 8-31-96 - Re RBP at 6240' perforations 9-1-3-96 - Rel to 1500 psi. and perforat 10 and 5114' tubing. Set iron control	gged up wireline. lows: 6162-6174' TOOH with casing ng. Set RBP at 64 6260-6316' with eleased packer. 7 . Tested RBP to 6162-6173' with Swabbed. Shut we leased packer and TOOH with packer and TOOH with packer to 5042-5114' w/ . TOOH with 4" of packer at 4977' HCL acid. Swabb	. TIH with 4" casing guns and perfor , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIH 420' and tested to 1500 psi. Set pa 2000 gallons 7-1/27 iron control ac TIH and circulated off RBP. Unset F 1500 psi. Pulled up and set packer 1500 gallons 7-1/27 NEFE acid and b 11 in. washed balls off RBP. Moved and set er and tubing. Rigged up wireline. 10 .42" holes as follows: 5042, 53, casing guns and rigged down wireline. Acidized perforations 5042-5114'	 P. and 6306-6316' (1 SPF - l with RBP, packer and acker at 6233'. Acidized and ball sealers. RBP. Pulled up and reset at 6102'. Acidized ball sealers. Swabbing. RBP at 5277'. Tested RBP TIH with 4" casing guns 54, 84, 88, 96, 5102, 06, and the sealer and 		
une suburface here 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin perforations Swabbing. 8-31-96 - Re RBP at 6240' perforations 9-1-3-96 - Rel to 1500 psi. and perforat 10 and 5114' tubing. Set iron control	gged up wireline. lows: 6162-6174' TOOH with casing ng. Set RBP at 64 6260-6316' with eleased packer. 7 . Tested RBP to 6162-6173' with Swabbed. Shut we leased packer and TOOH with packer and TOOH with packer to 5042-5114' w/ . TOOH with 4" of packer at 4977' HCL acid. Swabb	TIH with 4" casing guns and perford , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIH 420' and tested to 1500 psi. Set para 2000 gallons 7-1/27 iron control ac TIH and circulated off RBP. Unset F 1500 psi. Pulled up and set packer 1500 gallons 7-1/27 NEFE acid and b 11 in. washed balls off RBP. Moved and set er and tubing. Rigged up wireline. 10 .42" holes as follows: 5042, 53, casing guns and rigged down wireling. Acidized perforations 5042-5114' bed. Shut well in.	 and 6306-6316' (1 SPF - l with RBP, packer and acker at 6233'. Acidized and ball sealers. RBP. Pulled up and reset at 6102'. Acidized ball sealers. Swabbing. RBP at 5277'. Tested RBP TIH with 4" casing guns 54, 84, 88, 96, 5102, 06, and with 1500 gallons 7-1/2X 		
une suburface here 8-30-96 - Ri holes as fol Delaware). 2-7/8" tubin perforations Swabbing. 8-31-96 - Re RBP at 6240' perforations 9-1-3-96 - Rel to 1500 psi. and perforat 10 and 5114' tubing. Set iron control	gged up wireline. lows: 6162-6174' TOOH with casing ig. Set RBP at 64 6260-6316' with eleased packer. 7 . Tested RBP to 6162-6173' with Swabbed. Shut well leased packer and TOOH with pack ted 5042-5114' w/ . TOOH with pack . TOOH with 4" of packer at 4977' HCL acid. Swable fargoing is provid current Mention of the second a Size office the	TIH with 4" casing guns and perford , 6167-6173', 6260-6270', 6284-6290 guns and rigged down wireline. TIH 420' and tested to 1500 psi. Set para 2000 gallons 7-1/27 iron control ac TIH and circulated off RBP. Unset F 1500 psi. Pulled up and set packer 1500 gallons 7-1/27 NEFE acid and b 11 in. washed balls off RBP. Moved and set er and tubing. Rigged up wireline. 10 .42" holes as follows: 5042, 53, casing guns and rigged down wireling. Acidized perforations 5042-5114' bed. Shut well in.	 and 6306-6316' (1 SPF - l with RBP, packer and acker at 6233'. Acidized and ball sealers. RBP. Pulled up and reset at 6102'. Acidized ball sealers. Swabbing. RBP at 5277'. Tested RBP TIH with 4" casing guns 54, 84, 88, 96, 5102, 06, and with 1500 gallons 7-1/2X 		

.

. . _____

•

•

*See instruction on Reverse Side

				TRANSACTION REPORT		CCI-18-96 FRI 4:38 F	1-00 DM	
		F(FOR: OCD HOBBS		15053	930720	C10-90 FRI	4.JO IM
ĐA'	TE	START	SENDER	RX TIME	PAGES	TYPE	NOTE	
00T-	-18	4:36 PM	5059822047	1′27″	2	RECEIVE	0K	