

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Postage, Sec., T., R., M., or Survey Description)

800' FNL & 1650' FEL of Section 35-T19S-R32E (Unit B, NWNE)

FORM APPROVED

Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-59392

6. If Indian, Allotment or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Lusk AHB Federal #1

9. API Well No.

30-025-30808

10. Field and Pool, or Exploratory Area

Undesignated Delaware

11. County or Parish, State

Lea Co., NM

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION	
☐ Notice of Intend	☐ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment Notice	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut-Off
	☐ Altering Casing	☐ Conversion to Injection
	☒ Other Perforate & acidize	☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form 1)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give azimuthal locations and measured and true vertical depths for all markers and curves pertinent to this work.)

9-11-96 - Released packer. TIH and washed off RBP. Released and moved RBP. Reset RBP at 4650'. Tested RBP to 2000#. TOOH with packer and tubing. Rigged up wireline. TIH with 4" casing guns and perforated 4580-4600' w/21 .42" holes (1 SPF). TOOH with casing guns and rigged down wireline. TIH with packer and tubing. Set packer at 4527'. Shut in. 9-12-96 - Acidized perforations 4580-4600' with 1000 gallons 7-1/2% iron control acid and ball sealers. Swabbing. 9-13-96 - Swabbed. Released packer and RBP. TIH to 5010'. No sand on CIBP. TOOH with packer, RBP and tubing. Shut well in. Released well to production department.

14. I hereby certify that the foregoing is true and correct

Signed

(This space for Federal or State office use)

This Operations Technician

Date Sept. 16, 1996

Approved by

Conditions of approval, if any:

Title

Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side

```
*****  
*                                                                 P.01  
*                               TRANSACTION REPORT  
*                               _____  
*                                OCT-18-96 FRI   2:08 PM  
  
*                FOR: OCD HOEBS                        15053930720  
*_____  
*    DATE      START  RECEIVER          TX TIME  PAGES TYPE       NOTE  
*_____
```

OCT-18	2:08 PM	15058278177	**' **"	0	SEND	CANCEL
--------	---------	-------------	---------	---	------	--------

```
*_____
```