

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OFFICE FOR NUMBER
OF COPIES REQUIRED
(Other instructions on reverse side)

BLM Roswell District
Modified Form No.
M160-3160-4

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR YATES PETROLEUM CORPORATION		3a. Area Code & Phone No. 505/748-1471	
3. ADDRESS OF OPERATOR 105 South 4th St., Artesia, NM 88210		8. FARM OR LEASE NAME Flood AFN Federal	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 330' FSL & 660' FWL, Sec. 30-T19S-R32E		9. WELL NO. 1	
14. PERMIT NO. 30-025-30944		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3517.5' GR	
10. FIELD AND POOL, OR WILDCAT West Luks Delaware		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit M, Sec. 30-T19S-R32E	
12. COUNTY OR PARISH Lea		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETION

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 26" hole 5:00 PM 7-16-90 with rathole. Set 40' of 20" conductor. Resumed drilling 17½" hole 8:00 PM 7-17-90.
7-18-90. Ran 19 joints 13-3/8" J-55 ST&C 54.5# casing set at 707'. Guide shoe set 707', insert float set 755'. Cemented w/450 sx Pacesetter Lite C w/1% CaCl2 + 1/4#/sx Celloseal (yield 1.98, wt 12.4). Tailed in w/200 sx Class C w/2% CaCl2 (yield 1.32, wt 14.8). PD 4:15 AM 7-19-90. Bumped plug to 600 psi, held okay. Circulated 92 sacks cement. WOC. Drilled out 4:15 PM 7-19-90. WOC 12 hrs. Reduced hole to 12-1/4" and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Production Supvr.

DATE 7-24-90

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side