
Form 3160-5 (August 1999)

UNITED STATES UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT BUREAU OF LAND MANAGEMENT 1361 W. Grantus Avenues

gi W. G intesia, I	rand Avenue92
dicosia, i	M. If A. A. A. Otee or Tribe Name
	7. If Unit or CA/Agreement, Name and/or

SUNDRY NOTICES AND REPORTS ON WELLS AT LESIA, Notice of Tribe Name abandoned well. Use Form 3160-3 (APD) for such proposals.									
SUBMIT IN TRIPLICATE - Other instructions on	7. If Unit or CA/Agreement, Name and/or No.								
Ja. / tauress	8. Well Name and No. Lusk SWD #4 9. API Well No. 30-025-31051 10. Field and Pool, or Exploratory Area SWD - Delaware								
660' FNL & 2310' FWL of Section 35-T19S-R32E 12. CHECK APPROPRIATE BOX(ES) TO INDICATE	Lea Co., NM								
TYPE OF SUBMISSION	TYPE OF ACTION								
Acidize Deepen Acidize Deepen Alter Casing Fracture Tr Casing Repair New Const Change Plans Plug and A Final Abandonment Notice Convert to Injection Plug Back	ruction Recomplete Other								
13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) Propose to plug and abandon as follows: 1. TOOH with plastic coated tubing and nickel plated packer. 2. TIH with wireline and set a CIBP at 6334'. TOOH. TIH with tubing and tag CIBP. Load hole with plugging mud. Spot a 5 sack Class C cement plug from 6334-6299'. TOOH. 3. TIH with wireline and set a CIBP at 4683'. TOOH. TIH with tubing and tag CIBP. Spot a 50 sack Class C cement plug from 4683-4298' (across intermediate casing shoe). TOOH. 4. TIH with tubing. Spot a 25 sack Class C cement from from 2850-2700'. WOC. TIH and tag plug. Respot if necessary. NOTE: This plug will be across stage tool. 5. TIH with tubing. Spot a 30 sack Class C cement plug from 1192-999'. WOC. TIH and tag plug. Respot if necessary. NOTE: This plug will be across surface casing shoe. 6. Pressure test 5-1/2" casing to 1000 psi to ensure casing is plugged. If the casing will not pressure test, set a cement retainer at 850'. Establish an injection rate and squeeze with 45 sacks of Class C Neat cement. Sting out of retainer. Leave as acks of cement on retainer. 14. Thereby certify that the foregoing is true and correct.									
Name (Printed/Typed) Rusty Klein	Title Operations Technician								
Signature Mustry Helin	Date November 7, 2001								
THIS SPACE FOR FEDERAL OR STATE OFFICE USE									
Approved by Conditions of approval, if any, are attached. Approval of this notice does not warr certify that the applicant holds legal or equitable title to those rights in the subject which would entitle the applicant to conduct operations thereon.	PETROLEUM ENGINEER Date NUV 1 4 2001 ant or lease Office								



YATES PETROLEUM CORPORATION Lusk SWD #4 Section 35-T19S-R32E Lea County, New Mexico

SUNDRY NOTICE CONTINUED:

- 7. Spot a 15 sack Class C cement plug at surface.
- 8. Install regulation abandonment marker.

NOTIFY BLM-HOBBS (505-393-3612) AND OCD-HOBBS (505-393-6161, Ext. 112) 24 HOURS PRIOR TO COMMENCING PLUGGING OPERATIONS

Rusty Klein

Operations Technician November 7, 2001

			-				7
1		•					
	WELLNAME:	LUSK SU	JD#4	FIEL	.D:		
1.4	LOCATION:	660 FNL 1	2310 FW	L. Sec 35 Ti	95, h)32E	LEA Co	NM
	GL: 3573	ZERO; <u>/5</u>				46/4/0 000 0004	
	SPUD DATE: COMPLETION DATE:				CASING PROGRAM		
W4.		Compleated		11 /n 1992	II	/T/GR/CONN 5 [#] ゴ・SS STC /	DEPTH SET
	Lonver led	to SWD in	11114	76"			
		(1%1 /1	71. 1 × 1 /	1 7	8 5/8" 32"	11C-80, 446 J-55	3
		3//		>{			
	17/2	경되기	11 12/2	155	5/2 15.5	₹5-55 5-33	7860
	17/2	\{\ / \ \ \		Saz 1054 250 50]		
				3/2"	Life,	Be (ule
				13 /8 6 1142	"ω\ 950 sx, Cir	د	
		(<)			
		1<1		(
		52) stande @ 2	799		
	12/4	(X))- Toc 4,265'	· · ·		
){ {		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			
) 25/."	51 W 425 SK 2nd W	. 17 CO CY	
				878644651	-ω\425 sk) *** ω'	(7/303)	
		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	X)	- Nickal Flatcol	Insection Packer é	· 11/20	
					accumit pack on to	5. 46.30	
			/\				
	44					• ,	
	· /						
	•	1/					
			1/	- 4,733 - 5,138'((42)		
*** ***	.v.		12/			et a series	
	- (4년) - 1년						
Ç.	7/					G:	
	7 1/8)(-	
				6,384 - 7678' (₹/३)	<i>.</i> ·	
)<	\(
		(/	/)				
)>	\;(
		5<1	1/7				
		(/ -	(8/4'				
		(∠ 15		11 @ 7360' 181	1 500 SK Circ 2 nd	tal\ 7.75.5x	

