Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED		
Budget Bureau No. 1004-0135		
Expires: March 31 1993		

5. Lease Designation and Serial No.

NM 50302

		NM 39392	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals		6. If Indian, Allottee or Tribe Name	
		7. If Unit or CA, Agreement Designation	
SUBMIT IN TRIPLICATE			
1. Type of Well			
Oil Gas Well Other SWD WELL		8. Well Name and No. Lusk AHB Federal #4	
2. Name of Operator		9. API Well No.	
YATES PETROLEUM CORPORATION	(505) 748-1471)	30-025-31051	
3. Address and Telephone No.		10. Field and Pool, or Exploratory Area	
105 South 4th St., Artesia, NM 88210 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		East Lusk Delaware	
		11. County or Parish, State	
Unit C, 660' FNL, 2310' FWL, Sec. 35-T19S-R32E			
		Lea County, NM	
2. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA	
TYPE OF ACTION			
TYPE OF SUBMISSION	TIFE OF AUTON		
Notice of Intent	Abandonment	Change of Plans	
	Recompletion	New Construction Non-Routine Fracturing	
X Subsequent Report	Plugging Back	Water Shut-Off	
	Casing Repair Altering Casing	Conversion to Injection	
Final Abandonment Notice	Other	Dispose Water	
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	
12. Describe Proposed or Completed Operations (Clearly state a	Il pertinent details, and give pertinent dates, including estimated date of starting the starting of the starting to this work.)*		
give subsurface locations and measured and true vertice	cal depuis for all markers and zones permient to and workly		
6-23-92. RUPU. RU stripper and lay down rods and pump. NU BOP. TOH w/2-7/8" tubing			
anchor. TIH w/2-7/8" tubing to 7803'. Notified Bonnie Pritchard, NMOCD, Hobbs, NM,			
1 to 1 semmenced			
6-24-92. TOH and laid down 2-7/8" production string. Picked up 2-7/8" plastic-coated			
6-24-92. TOH and Taid down 2-7/8 production string. Treated appears to injection stirng. Set nickel-plated packer on 2-7/8" J-55 plastic coated tubing at 4668'.			
ND BOP. NU tree. Loaded annulus and tested to 600 psi for 30 minutes. Rigged down. NOTE: Notified Bonnie Pritchard, NMOCD, Hobbs, NM, to witness test, but test was not			
NOTE: Notified Bonnie Pritch	hard, NMOCD, HODDS, NM, to withess to	ac, but been made and	
witnessed - ran chart.			
WELL APPROVED BY NMOCD SWD N	0.480.		
WELL AFFROVED DI MIOOD BUD I			
		englight terres of the	
	Av	2	
•		militaria, internativa di Salamania. Periodenia	
en e			
		A CALL CALL CALL SAN YOUR	
14. I hereby certify that the foregoing is true and correct			
signed and and by the	Title Production Supervisor	Date <u>7-7-92</u>	
(This space for Federal or State office use)			
	Title	Date	
Approved by			