

DISTRICT I

State of New Mexico  
Energy, Minerals and Natural Resources Department

P.O. Box 1980, Hobbs NM 88240

DISTRICT II

P.O. Drawer DD, Artesia NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO 30-025-31073

5. Indicate Type of Lease

State ☒ FEE

6. State Oil & Gas Lease No.

VB-11

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name

1. Type of Well:

OIL GAS  
WELL ☒ WELL OTHER

HOURGLASS AEG STATE

2. Name of Operator

**Yates Petroleum Corporation**

8. Well No

1

3. Address of Operator

**105 South 4th., Artesia, NM 88210**

9. Pool Name or Wildcat

VACUUM WOLFCAMP, SOUTH

4. Well Location

Unit Letter A : 660 Feet From The NORTH Line and 660 Feet From The EAST Line

Section 16 Township 18S Range 35E NMPM LEA COUNTY

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3919' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK PLUG AND ABANDON ☒

TEMPORARILY ABANDON CHANGE PLANS

PULL OR ALTER CASING

OTHER

SUBSEQUENT REPORT OF:

REMEDIAL WORK ALTERING CASING

COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT

CASING TEST AND CEMENT JOB

OTHER

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

YATES PETROLEUM CORPORATION proposes to plug & abandon as follows:

1. MIRU PU - RU safety equipment.
2. RU wireline; RIH w/ 5-1/2" CIBP & set @ 9700'. Dump 35' cement on plug.
3. TIH w/ tubing & circ hole w/ 9.5 ppg mud.
4. RU cementers, pull up & spot 100' cement plug 6135- 6035'. - TAG
5. Pull up & spot 100' cement plug 3862-3762'.
6. Spot 100' cement plug 1856-1756'. WOC & tag-
7. Perf holes @ 465'. Squeeze & spot 100' cement plug 465-365'. TAG
8. Spot 10 sack cement plug at surface.
9. Cut off wellhead & install regulation marker.

THE COMMISSION MUST BE NOTIFIED 24  
HOURS BEFORE THE BEGINNING OF  
PLUGGING OPERATIONS FOR THE C-103  
TO BE APPROVED.

I hereby certify that the information above is a true and complete to the best of my knowledge and belief

SIGNATURE *Donna Clack*

TITLE *Operations Technician*

DATE *5/3/02*

TYPE OR PRINT NAME *DONNA CLACK*

TELEPHONE NO. *505-748-1471*

(This space for State Use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

ORIGINAL SIGNED BY  
GARY W. WINK  
OC FIELD REPRESENTATIVE II/STAFF MANAGER

DATE

**MAY 13 2002**

