

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit J, 2310' FSL & 1650' FEL, Sec. 35-T19S-R32E, NMPM

5. Lease Designation and Serial No.

NM 59392

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Lusk AHB Federal #3

9. API Well No.

30-025-31111

10. Field and Pool, or Exploratory Area

East Lusk Delaware

11. County or Parish, State

Lea, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Set 5-1/2" casing
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

RS 7900'. Reached TD 2-14-92. Ran 181 joints 5-1/2" 15.5# and 17# J-55 LT&C casing set 7900'. Float shoe set 7900'. Float collar set at 7854'. DV tool set 4527'. Cemented in two stages: Stage 1: 500 g. WMW-1, 500 g. Surebond, 675 sx "H", 8# CSE, .6% CF-14, 1/4#/sx Celloseal, 5#/sx Gilsonite and .35% Thrifty Lite (yield 1.75, wt 13.50. PD 7:30 AM 2-15-92. Circulated thru DV tool 3-1/2 hrs. Stage 2: 470 sx Pacesetter Lite "C" Neat (yiedl 1.98, wt 12.4). Tail in w/100 sx "C" Neat (yield 1.32, wt 14.8). PD 12:00 PM 2-15-92. Closed tool with 3000#. Casing and float held OK. Circulated 136 sacks to pit. WOC 18 hrs.

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Supervisor

Date 2-20-92

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

RECEIVED

MAR 12 1992

100 HOBBS STREET