

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Hanley Petroleum Inc.

3. Address and Telephone No.

415 W. Wall, Suite 1500, Midland, TX 79701 (915) 684-8051

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FSL & 330' FWL, Sec. 24, T-18-S, R-32-E
NMPM

5. Lease Designation and Serial No.

NM 64598

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Hanley 24 Federal #1

9. API Well No.

30 025 31115

10. Field and Pool, or Exploratory Area

Querecho Plains-Upper Bone

11. County or Parish, State

Lea, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other Drig & setting csg.
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1-2-91 Drld 11" hole to 3015'. 3/4 deg. @ 3015' Ran 8-5/8" csg as follows: Howco Float shoe (1.85') 1 jt 8-5/8" 32# K-55 csg (44.00') Howco float collar (1.00') 25 jts 8-5/8" 32# K-55 csg (1097.64') 42 jts 8-5/8" 24# K-55 csg (1845.25') 1 jt 8-5/8" 32# K-55 csg (42.90'). Set csg @ 3015'. Halliburton cmtd w/925 sx Howco lite w/15# salt & 1/4# flocele/sx plus 200 sx Cl C w/2% CaCl2. Cmt in place @ 11:10 P.M. 1-2-91. Did not bump plug. Floats held o.k. Circ 125 sx cmt to pits. Set csg head & NU BOP.
- 1-3-91 Tested blind rams to 2000 psi. Held O.K. Tested 8-5/8" csg to 1055 psi. Held o.k. Drld out float collar & tested to 1500#. Held O.K. Drld float shoe & 5' formation. Tested shoe to 350 psi. (11.0# mud equivalent). Held O.K. Drld formation to 3359'.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Vice President Production

Date

1-7-91

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side