

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Hanley Petroleum Inc.

3. Address and Telephone No.

415 W. Wall, Suite 1500, Midland, Texas 79701 (915) 684-8051

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FSL & 330' FWL, Sec. 24, T-18-S, R-31-E
NMPM

5. Lease Designation and Serial No.

NM 64598

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Hanley 24 Federal #1

9. API Well No.

30 025 31115

10. Field and Pool, or Exploratory Area

Querecho Plains-Upper Bone Spr.

11. County or Parish, State

Lea, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other Spud and Drilling
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 12-29-90 Spudded 17-1/2" hole @ 9:30 A.M. Drilled to 410'. Ran 10 jts 13-3/8" 48# H-40 csg & set @ 410'. Halliburton cmt w/400 sx Cl C cmt w/2% CaCl2. PD @ 5:45 P.M.
12-29-90. Circ 120 sx cmt to pits. Jack Johnson w/BLM witnessed.
12-30-90 NU BOP stack. Tested blind rams to 1200#. Ran 11" bit & [20] 8" DC's. Tagged cmt @ 362'. Drilled out cmt & tested pipe rams to 1200#. Held O.K. Drilled to 1240'. Dev. Sur. 1-1/2 deg. @ 615', 1-1/4 deg. @ 1240'.
12-31-90 Drlg @ 2579' in anhydrite & lime. Dev. Sur. 3/4 deg. @ 1408', 3/4 deg. @ 1904', 1-1/4 deg. @ 2402', 2 deg. @ 2555'.
1-1-91 Drlg @ 2927' in anhydrite & lime. Dev. Sur. 2-1/4 deg. @ 2678', 1-3/4 deg. @ 2833'.

14. I hereby certify that the foregoing is true and correct.

Signed

(This space for Federal or State office use)

Approved by

Conditions of approval if any

Vice President Production

Date 1-2-91

Date