

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.  
NM 59392

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Lusk AHB Federal #5

9. API Well No.

30-025-31151

10. Field and Pool, or Exploratory Area

East Lusk Delaware

11. County or Parish, State

Lea, NM

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit B, 330' FNL & 1980' FEL, Sec. 35-T19S-R32E

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☒ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded 26" hole 3:30 PM 11-19-91. Set 40' of 20" conductor. Cement to surface with redi-mix. Notified BLM, Hobbs, NM, of spud. Resumed drilling 17½" hole 7:00 PM 11-21-91. Ran 26 joints 13-3/8" 54.5# J-55 casing set 1140'. Guide shoe set 1140', float collar set 1098'. Cemented w/700 sx Pacemaker Lite "C" + 2% CaCl<sub>2</sub> + 1/4#/sx Celloseal (yield 1.76, wt 12.9). Tailed in w/250 sx "C" + 2% CaCl<sub>2</sub> (yield 1.32, wt 14.8). PD 11:59 AM 11-23-91. Bumped plug to 600 psi, float held OK. Circulated 225 sacks cement. WOC. Drilled out 4:30 AM 11-25-91. WOC 40 hrs and 31 mins. NU and tested to 500 psi for 15 minutes. Reduced hole to 12-1/4" and resumed drilling.

5  
EVB

14. I hereby certify that the foregoing is true and correct

Signed

*[Signature]*

Title Production Supervisor

Date 11-25-91

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side