

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy Rustler 1808	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn 10955	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka 11055	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates 3208	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen 4352	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres 4963	T. Simpson _____	T. Gallup _____	T. Ignacio Otzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinbry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Delaware Sand 5360	T. Todilto _____	T. _____
T. Drinkard _____	T. Bone Springs 6502	T. Entrada _____	T. _____
T. Abo 9758	T. _____	T. Wingate _____	T. _____
T. Wolfcamp 10111	T. _____	T. Chinle _____	T. _____
T. Penn 10713	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....
 No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	350	350	Surface, Rock, Redbeds	8700	9330	630	SS, Dolo, Sltst, Cht
350	1464	1114	Salt, Anhy	9330	9510	180	Dolo, Sh, LS
1464	3900	2436	Anhy, Dolo, LS	9510	9610	100	SS, Dolo
3900	4250	350	Dolo, Anhy	9610	9840	230	Sh, LS, Dolo
4250	4380	130	Dolo, Anhy, Sh	9840	9930	90	Dolo
4380	4420	40	SS, Dolo, Anhy	9930	10570	640	LS, Sh, Cht
4420	4590	170	Dolo, Anhy	10570	10960	390	Sh, LS
4590	4910	320	Dolo, Anhy, SS	10960	11130	170	Cong
4910	4980	70	Dolo, Snhy, Cht	11130	11300	170	Sd, Sh, LS
4980	5450	470	Dolo, Sd				
5450	5520	70	Dolo, Sd, Cht				
5520	5700	180	LS, SS, Cht				
5700	6070	370	SS, Dolo				
6070	6440	370	Sh, SS, Dolo				
6440	6520	80	Dolo				
6520	6740	220	LS				
6740	6860	120	Dolo, Sh, LS				
6860	7354	494	Dolo, Sh, LS, Cht				
7354	7770	416	Dolo, LS, Cht, Sh				
7770	8380	610	Sh, Cht, Dolo				
8380	8700	320	SS, Dolo				