

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31244
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-7653

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter <u>P</u> : <u>660</u> ⁸⁶⁰ Feet From The <u>South</u> Line and <u>860</u> ⁹⁹⁰ Feet From The <u>East</u> Line

7. Lease Name or Unit Agreement Name Nowata AGR State
8. Well No. 1
9. Pool name or Wildcat Wildcat Bone Springs

Section <u>9</u>	Township <u>18S</u>	Range <u>35E</u>	NMPM	Lea	County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3920' GR					

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Set production casing, perforate, trt <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 10910'. Reached TD 3-21-93. Ran 266 joints 7" 26# N-80, J-55 and S-95 casing set at 10910'. Float shoe set 10910', float collar set 10868'. Howco "ES" DV tools set 9102' and 7637'. Cmt'd in 3 stages. Stage I: 275 sx "H" w/8#/sx CSE, .9% CF-14, .35% Thriftylite, 8#/sx Gilsonite (yield 1.73, wt 1.37). PD 10:01 PM 3-23-93. Bumped plug to 1200 psi, held OK. Circulated 52 sacks. Circulated thru DV tool 3 hrs. Stage II: 300 sx "H" w/8#/sx CSE, .65% CF-14, .35% Thriftylite, 8#/sx Gilsonite (yield 1.73, wt 13.7). PD 2:13 AM 3-24-93. Bumped plug to 2500 psi for 1 min. Circulated 75 sacks. Circulated thru DV tool 3 hrs. Stage III: 675 sx PSL "C" w/.4% CF-14, 5% Salt (yield 2.01, wt 12.5). Tailed in w/150 sx "C" (yield 1.32, wt 14.8). PD 6:50 AM 3-24-93. Bumped plug to 3000 psi for 1 min. Float and casing held. WOC 24 hrs. Drilled DV tools at 9102' and 7637'. Perforated 10318-10332' w/4 SPF. Acidized perfs 10318-332' w/2000g. 20% NEFE acid. Recovered load. Set retainer wireline at 10268'. WIH w/stinger on 2-7/8" tubing. Cemented perfs 10318-332' w/75 sx w/.5% Halad-9 and 75 sx Class "H" Neat. Squeezed to 2000 psi. Perforated 8282-8290' w/4 SPF total 32 - .42" holes. Acidized perforations 8282-8290' w/2000g. 20% NEFE acid.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 4-2-93

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY Paul Kautz Geologist TITLE Geologist DATE APR 06 1993

CONDITIONS OF APPROVAL, IF ANY: