

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31244 ✓
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-7653
7. Lease Name or Unit Agreement Name Nowata AGR State
8. Well No. 1
9. Pool name or Wildcat Wildcat Strawn

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter P : 660 860 Feet From The South Line and 660 990 Feet From The East Line Section 9 Township 18S Range 35E NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3920' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
OTHER: <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
	COMMENCE DRILLING OPNS. <input type="checkbox"/>
	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 85 joints of 9-5/8" 36# & 40# casing (3842.90') of casing set at 3838'. 1-Texas Pattern Notched guide shoe set at 3838'. Float collar set at 3792'. Cemented with 1250 sacks Pacesetter Lite "C" with 1/4#/sack celloseal (yield 1.92, weight 12.5). Tailed in with 250 sacks "C" and 2% CaCl2 (yield 1.32, weight 14.8). PD 6:30 PM 2-12-93. Bumped plug to 1600 psi, OK. Circulated 150 sacks. WOC 24 hours and 30 minutes. Drilled out at 7:00 PM 2-13-93. Nipped up and tested to 1000 psi for 30 minutes, OK. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Clerk DATE Feb. 26, 1993

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

Orig. Signed by Paul Kartz Geologist

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

MAR 02 1993