

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31244
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-7653
7. Lease Name or Unit Agreement Name Nowata AGR State
8. Well No. 1
9. Pool name or Wildcat Wildcat Strawn

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter P : 660 860 Feet From The South Line and 660 990 Feet From The East Line Section 9 Township 18S Range 35E NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3920' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 2-2-93. Set 40' of 20" conductor pipe. Redi-mix to surface. Notified NMOCD, Hobbs, NM, of spud. Resumed drilling 17-1/2" hole 7:30 PM 2-4-93. Ran 10 joints 13-3/8" 54.5# casing set 450'. Guide shoe set 450', insert float set 402'. Cemented w/150 sx "H" w/12% Thixad, 1/4#/sx Celloseal, 5#/sx Gilsonite, 3% CaCl2 (yield 1.43, wt 15). Tailed in w/400 sx "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 1:15 AM 2-5-93. Bumped plug to 400 psi, float held OK. Circulated 88 sacks. WOC. Drilled out 9:30 PM 2-5-93. WOC 20 hours and 15 minutes. NU and tested to 500 psi for 15 minutes. OK. Reduced hole to 12-1/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 2-10-93
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

Orig. Signed by
Paul Kautz
Geologist

APPROVED BY _____ TITLE _____ DATE FEB 15 1993

CONDITIONS OF APPROVAL, IF ANY: