

WELL

ELD

ATE

ANDAWAY '25' FEDERAL 1

SOUTH SALT LAKE

SEPT. 16, 1991

MTJ.

WELL CLASS

☒ PRESENT COMPLETION☐ SUGGESTED COMPLETION☐ ORIGINAL COMPLETION

OIL

PERMANENT WELL  
BORE DATA

GR. 3581.1

KB 3596.3

## DATA ON THIS COMPLETION

## 1. LOCATION:

SESE SEC. 25 T19S-R 32E  
LEA COUNTY, NEW MEXICO  
660 FSL, 1660 FEL

## 2. CASING DETAILS:

13 $\frac{3}{8}$ " 48" H-40 STC, 11jts - 500'

8 $\frac{5}{8}$ " 32" K-55, 81jts } 4510'  
32" S-80, 23jts. }  
DV Tool @ 3240'

5 $\frac{1}{2}$ " 17" N-80 LTC 183jts. 7902.63'

## 3. CEMENT DETAILS:

13 $\frac{3}{8}$ " 450 SX. LITE, TO SURFACE8 $\frac{5}{8}$ " 1<sup>st</sup> STAGE 400 SX.2<sup>nd</sup> STAGE 1600 SX.

NOTE: TOC @ 650', RIH W/ 1"

AND CMT'd W/ 230 SX. 'C' NEAT

14.3 PPG - Tagged CMT 20' FROM SURFACE.

5 $\frac{1}{2}$ " 1100 SX. 50/50 P&Z

TOC @ 2400' by Bond log.

RAN 40 CENTRALIZERS AS FOLLOWED.

1 - ON FLOAT JOINT

1 - EVERY 3<sup>rd</sup> JOINT TO 5700'

1 - EVERY JOINT 5700'-5000'

1 - EVERY 3<sup>rd</sup> JOINT 5000'-4500'

## Production Equipment:

M-640 Pumping Unit

2 - 500 BBL STEEL, OIL TANKS

1 - 400 BBL FIBERGLASS WTR TANK

1 - 4X20' VERT. TREATER.

## Tubing Details:

163jts 2 $\frac{7}{8}$ " N-80 ABC Tbg.

ANCHOR @

3jts Tbg

SN @ 5108'

3' PERF SUB

MUD ANCHOR (Bull Plugged)

(Btm of Tbg @ 5142')

## RODS:

90-3/4"; 66-7/8"; 47-1"

Pump: INSERT 2 $\frac{1}{2}$ X1 $\frac{3}{4}$ X24'