Submit 3 Copies to Appropriate District Office

1. Type of Well: WELL X

4 Well Location

11.

OTHER:

2. Name of Operator

MERIDIAN OIL INC.

Unit Letter N

Section 15

PERFORM REMEDIAL WORK

TEMPORARILY ABANDON

PULL OR ALTER CASING

work) SEE RULE 1103.

Address of Operator

State of New Mexico Energy, Minerals and Natural Resources Department

DISTRICT

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

1000 Rio Brazos Rd., Aztec, NM 87410

GAS WELL

P.O. Box 51810, Midland, TX

Form C-103 Revised 1-1-89 OIL CONSERVATION DIVISION WELL API NO. P.O. Box 2088 30-025-31380 Santa Fe. New Mexico 87504-2088 5. Indicate Type of Lease STATE FEE 6. State Oil & Gas Lease No. V8-161 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) PERCHA 15 STATE OTHER 8. Well No. 2Y 9. Pool name or Wildcat 79710-1810 CORBIN BONESPRING SOUTH 660 Feet From The SOUTH 1830 Feet From The WEST Line and Township 18-S Range 33-E NMPM LEA 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3875.4' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PLUG AND ABANDON REMEDIAL WORK **ALTERING CASING CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB X OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed 9-01-91 SPUDDED 17 1/2" HOLE. DRLD TO 436'. RAN 13 3/8" 48# H-40 STC CSG & SET @ 436'. CMTD W/425 SXS " C" CMT, 2% CACL2 + 1/4#/SK CELLO-FLAKE. CIRCD 140 SXS TO SURFACE. USED 4 CENTNRALIZERS, WOC 18 HRS. Tested Csg +0 TOUT for Bomen. 9-04-91 DRLD 12 1/4" HOLE TO 2904'. RAN 68 JTS 8 5/8" 28# K-55 BTC CSG & SET @ 2904'. CMTD CSG W/1100 SXS C LITE + 6% GEL + 15 PPS SALT + 1/4 PPS CELLO-FLAKE TAILED BY 250 SXS "C" + 2% CACL2. CIRCD 260 SXS TO SURFACE. USED 4 CENTRALIZERS. WOC 18 HRS. BUMPED PLUG W/500-750 PSI. \circ κ . 9-26-91 DRLD 7 7/8" HOLE TO 11590'. RAN 265 JTS 5 1/2' 17# N-80 & K-55 LTC CSG & SET @ 11590'. CMTD W/ 365 SXS "C" CMT, 4% GEL, .8% FL-20, 2% R-3 TAILED BY 275 SXS "H" + 3% KCL + .9% FL-20 + 2% FWC-2. CIRCD TO DV TOOL @ 7014'. BUMPED PLUG W/750-1000 PSI FOR 30 MIN, OK. CMTD 2ND STAGE W/700 SXS C 2% A2, 5% SALT & 250 SXS C 2% FW22. TOC @ 3245' BY LOG. WOC 7 DAYS. BUMPED TO 1500 PSI FOR 30 MIN, OK. USED 24 plate to the best of my knowledge and belief.

DATE

I hereby certify that the information above TILE PRODUCTION ASST. DATE 12-06-91 TELEPHONE NO. 915-688-6906 TYPE OR PRINT NAME MARIA L. PEREZ

TILE

15:10

(This space for State Use)

CENTRALIZERS.

APPROVED BY -

CONDITIONS OF APPROVAL, IP ANY: