

SHGSAU TRACT 6 WELL 9 AREA OF REVIEW

OPERATOR	CROSS TIMBERS	CROSS TIMBERS	CROSS TIMBERS	CROSS TIMBERS	CROSS TIMBERS	
WELL NAME	SHGSAU TRACT 4 #13	SHGSAU TRACT 5 #7	SHGSAU TRACT 6 #1	SHGSAU TRACT 6 #2	SHGSAU TRACT 6 #3	
LOCATION	1485' FWL, 2400' FWL	2615' FWL, 2615' FWL	1980' PSL, 660' FWL	660' PSL, 1980' FWL	1980' PSL, 1980' FWL	
SEC/TRP/RGE	SEC 29, T17S, R33E	SEC 29, T17S, R33E	SEC 29, T17S, R33E	SEC 29, T17S, R33E	SEC 29, T17S, R33E	
WELL TYPE	OIL	OIL	INJECTION	INJECTION	INJECTION	
STATUS	SI	SI	P & A	P & A	SI	
SURFACE CSG.	8-5/8" 24# K-55 @ 1312'.	8-5/8" 24# K-55 @ 1300'	8-5/8" 32# @ 1265'	8-5/8" 32# @ 1300'	8-5/8" 32# @ 1260'.	
CMT SY.	800SX	660SX	50SX	25SX	50SX	
TOP OF CMT	SURFACE	SURFACE	1166' (CALC)	1250' (CALC)	1160' (CALC)	
INTERMEDIATE CSG						
CMT SY.						
TOP OF CMT						
PRODUCTION CSG	5-1/2" 15.5# K-55 @ 3907' 5-1/2" 15.5# K-55 @ 3888'		7" 22.5# @ 3960'	7" 22# @ 4060'	7" 22# @ 3950'	
CMT SY.	1000SX	1135SX	75SX	200SX	75SX	
TOP OF CMT	SURFACE	SURFACE	3030(CALC)(355 AFTER SQZ)	2200' (CALC)	SURFACE	
LINER	4" 10.46# J55 3676'-4449' 4" 11.34# N80 3696'-4379'	4" 11.34# N80 3696'-4379'	4-1/2 11.6# N80	4-1/2 11.6# N80	4-1/2 11.6# N80	
CMT SY.	50SX	50SX	200SX	400SX	75SX	
TOTAL DEPTH	4450'	4380'	4272'	4320'	4445'	
DATE DRILLED	9/81	12/79	9/43	4/43	12/43	
PERFORATIONS	4118'-4236'	4172'-4354'	4168-4238, OH 4253-4272	OH 4060'-4312' (4320'-12'	4236'-4326'	
REMARKS			SQZ 2379'-2409' W/2975SX IN 11/84. P & A 11/21/84. CIBP @ 4019'. 30SX 4019'-3705'. 100SX 3014'-2420'. CIBP @ 2204'. 220SX 2204'-897'. 25SX 806'-857'. 25SX 122'-SURF.	PE W/LEAD WOOL). P & A 3/82. RET @ 3995'. SQZ W/500SX. CSG COLLAPSED BELOW 2125'. CUT OFF 2-7/8" TBG @ 2110'. SQZ LK 208'-240' W/550SX. CIRC 150SX. PERP @ 2100'. RET @ 2000'. SQZ W/300SX. LEFT 4SX ON RET(TOC 1900'). PERP @ 1300'. RET @ 1265'. SQZ W/200SX. LEFT 25SX ON RET. PERP @ 500'. RET @ 425'. SQZ W/100SX. 100SX 425'-SURF.	SQZ 2505'-37' W/600SX. SQZ 1270' W/750SX. CIRC TO SURF. 3/83 SQZ @ 3020' W/200SX. SQZ @ 1183' W/700SX.	4/83 - SQZ @ 1265' W/200SX.