

SMGSAU TRACT 6 WELL 9 AREA OF REVIEW

OPERATOR	CROSS TIMBERS	CROSS TIMBERS	CROSS TIMBERS	CROSS TIMBERS	CROSS TIMBERS
WELL NAME	SMGSAU TRACT 6 #5	SMGSAU TRACT 6 #6	SMGSAU TRACT 6 #7	SMGSAU TRACT 6 #8	SMGSAU TRACT 7 #5
LOCATION	1330' PSL, 1330' PHL SEC 29, T17S, R33E	1310' PSL, 100' PHL SEC 29, T17S, R33E	1455' PSL, 1330' PHL SEC 29, T17S, R33E	125' PSL, 1345' PHL SEC 29, T17S, R33E	1395' PSL, 2615' PHL SEC 29, T17S, R33E
SEC/WFP/RGE					
WELL TYPE	OIL	OIL	OIL	OIL	OIL
STATUS	P & A	ACTIVE	ACTIVE	ACTIVE	P & A
SURFACE CSG.	10" 34# @ 20'	8-5/8" 24# @ 833'	8-5/8" 24# @ 1302'	8-5/8" 24.55# @ 309'	8-5/8" 34# @ 1281'
CHT SX.	0SX	400SX	660SX	250SX	50SX
TOP OF CHT	NA	SURFACE	SURFACE	SURFACE	1174' (CALC)
INTERMEDIATE CSG					
CHT SX.					
TOP OF CHT					
PRODUCTION CSG	7" 23# @ 4008'	5-1/2" 14# @ 4292'	5-1/2" 17# @ 3900'	5-1/2 15.5# @ 17# @ 4550'	7" 22# @ 4028'
CHT SX.	240SX	435SX	800 (SQZ @ 1315' W/500SX)	1170SX	100SX
TOP OF CHT	873(DV TOOL 1400' W/90SX)	2020'	SURFACE	SURFACE	2788' (CALC)
LINER	5" 15# 3840'-4189'		4" 10.46# 3728'-4360'		5-1/2" 4028'-4473'
CHT SX.	236SX		75SX		
TOTAL DEPTH	4320'	4292'	4360'	4550'	4473'
DATE DRILLED	8/47	1/73	9/80	12/91	1/44
PERFORATIONS	4189'-4320' (OH)	4170'-4271'	4177'-4326'	4257'-4382'	4232'-4300'
REMARKS	P & A 10/31/80. RET @ 3809. SQZ W/1000SX. LEPT 100SX ON RET. TOC @ 3148'. 125SX 3148'-2043'. RET @ 961'. SQZ W/500SX. PWP 400SX DWN CSG. 10SX 30'-SURP.				P & A 1/45 RE-PLUGGED 3/18/80 7" CASING CUT OFF @ 1622' 200SX 1313'-1675' 200SX 1020'-1313' 10SX 30'-SURFACE