

SMGSAU TRACT 6 WELL 9 AREA OP REVIEW

OPERATOR	R.D. COLLIER	BARNEY COCKBURN	PHILLIPS PETROLEUM CO.
WELL NAME	STATE #1-X	OHIO-JONES #2	U. S. MINERALS #5
LOCATION	330' FML, 330' FEL	1980' FML, 1980' FEL	990' FSL, 1650' FEL
SEC/TWP/RGE	SEC 31, T17S, R33E	SEC 30, T17S, R33E	SEC 30, T17S, R33E
WELL TYPE	OIL	DRY HOLE	OIL
STATUS	P & A	P & A	ACTIVE
SURFACE CSG.	8-5/8" 28# @ 1330'	8 5/8" 37# @ 1175'	8 5/8" 24# @ 1265'
CHT SY.	50SX	50SX	570SX
TOP OF CMT	1223' (CALC)	1068' (CALC)	SURFACE (CIRC)
INTERMEDIATE CSG			
CHT SY.			
TOP OF CMT	7" 20# @ 4015'	7" 20# @ 3937'	5 1/2" 17# & 15.5# @ 4449'
PRODUCTION CSG	100SX	100SX	950SX
CHT SY.			
TOP OF CMT	2775' (CALC)	2697' (CALC)	SURFACE (CIRC)
LINER			
CHT SY.			
TOTAL DEPTH	4314'	4304'	4500'
DATE DRILLED	4/50	10/44	3/80
PERFORATIONS	4015' - 4314' (OH)		4226' - 4425'
REMARKS	P&A 6/8/59 20SX 4314' - 3975' CUT OFF 7" @ 2100' 20SX @ 2100' 20SX @ 1326' 15SX @ SURFACE	RE-PLUGGED 7/81 DRL OUT TO 8 5/8" @ 246' SET 8 5/8" 24# @ 246' CHT W/ 225SX DRL OUT TO 7" @ 2323' DRL OUT 7" TO 3967' 100SX 3967' - 3887' 100SX 2453' - 2000' 100SX 1270' - 900' 100SX 346' - SURFACE	CIBP @ 4400'