

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-C25-31EC3 ✓
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. L-6691

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
Union Oil Company of California

3. Address of Operator
P.O. Box 671 - Midland, TX 79702

4. Well Location
Unit Letter A : 660 Feet From The north Line and 660 Feet From The east Line

Section 36 Township 19-S Range 32-E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3372.7' GR

7. Lease Name or Unit Agreement Name
State "HH" (Delaware)

8. Well No. 2

9. Pool name or Wildcat
Geronimo (Delaware)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☒
OTHER: ☐	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☒
	OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3/1 MIRU GRACE DRILG CO RIG #467. SPUD 17-1/2" SURF HOLE @ 5:30 PM 3-1-93. TD 17-1/2" SURF HOLE TO 505' @ 2:30 AM 3-2-93. CIRC 1/2 HR. POOH. RUN 13-3/8" CSG, INC.

3/2 2-1/2 HR FIN R&C 10 JTS + 1 PC (487') 13-3/8" 48# H-40 LSS 8RD ST&C NEW ERW CSG @ 503' W/ 400 SX CL "C" W/ 3# GEL, 2# CACL2 @ 13.8 PPG @ 4.5 BPM, 150-100 PSI. DISP RUBBER PLUG TO INSERT FLOAT @ 458' W/ 72 BFW @ 4.5-4 BPM, 100-150 PSI. BUMPED PLUG W/ 400 PSI, FLOAT HELD. PLUG DN & CIP @ 8:30 AM 3-2-93. CIRC 143 SX TO PIT. 4 HRS WOC. CUT OFF 13-3/8" CSG. 13-3/8" CSG MEAS TO BE 3-1/2", WH BORE WAS 13-1/2", WOULD NOT SLIP ON. SENT TO BLAIR MACHINE SHOP (HOBBS) & BORED TO 13-5/8" & BACK TO LOCATION. WELD ON CIW C-22 13-5/8" 3M X 13-1/2" SOW HD, NU SHAFFER 12" 3M DBL RAM BOP W/ SPOOLS, 12" GRANT ROTATING HD, INC.

3/3 FIN NU BOP. TST BLINDS, MANI & 13-3/8" CSG TO 1000 PSI, OK. TIH W/ BIT TO 450'. TST 4-1/2" PIPE RAMS & 13-3/8" CSG TO 1000 PSI, OK. DRILL PLUG & INSERT @ 458', 44' OF CMT & SHOE @ 503', ON FORM @ 3:00 PM 3-3-93. 30-1/2 HRS WOC. INSTALL ROTATING HD RUBBER & DRIVER.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Charlotte Beeson TITLE Drilling Clerk DATE 3-4-93
TYPE OR PRINT NAME Charlotte Beeson TELEPHONE NO. (915) 665-7667

(This space for State Use)

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON TITLE DISTRICT SUPERVISOR DATE
CONDITIONS OF APPROVAL, IF ANY:

MAR 09 1993