

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.  
30-025-31876

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
B-1733-2

7. Lease Name or Unit Agreement Name  
VACUUM GLORIETA WEST UNIT

8. Well No.  
121

9. Pool name or Wildcat  
VACUUM GLORIETA

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☐ OTHER WATER INJECTION

2. Name of Operator  
TEXACO EXPLORATION AND PRODUCTION INC.

3. Address of Operator  
P. O. Box 3109 Midland, Texas 79702

4. Well Location  
Unit Letter A : 964 Feet From The NORTH Line and 90 Feet From The EAST Line

Section 1 Township 18-SOUTH Range 34-EAST NMPM LEA County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
GR-3986', KB-4000'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  
**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: CORE & PRODUCTION CASING ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. DRILLED 7 7/8 HOLE TO 6343'. CUT FIVE CORES: 5982-6015, RECV. 30'. 6015-6042, RECV. 27.5'. 6144-6204, RECV. 60'. 6204-6229, RECV. 25'. 6229-6264, RECV. 35'. TD @ 12:30 PM 07-24-93.
2. HLS RAN GR-DLL-MSFL, GR-SDL-DSN-CSNG FROM 6342' TO 4350'. PULLED GR-DSN TO SURFACE.
3. RAN 20 JOINTS OF 5 1/2" 17# WC-50 AND 124 JOINTS OF 15.5#, LTC CASING SET @ 6343'.
4. DOWELL CEMENTED 1400 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 PPG, 1.94 CF/S). F/B 200 CLASS H (15.6 PPG, 1.18 CF/S). PLUG DOWN @ 9:30 PM 07-25-93. CIRCULATED 50 SACKS.
5. ND. RELEASE RIG @ 12:00 PM 07-25-93.
6. PREP TO COMPLETE.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE C.P. Basham / SDH TITLE DRILLING OPERATIONS MANAGER DATE 07-26-93

TYPE OR PRINT NAME C.P. BASHAM

TELEPHONE NO. 915-6884620

(This space for State Use)

Orig. Signed by  
Paul Kautz  
Geologist

APPROVED BY \_\_\_\_\_

TITLE \_\_\_\_\_

DATE JUL 29 1993

CONDITIONS OF APPROVAL, IF ANY: