

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.  
30-025-31891

5. Indicate Type of Lease  
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☒

GAS  
WELL ☐

OTHER

2. Name of Operator

Rand Oil & Gas, Inc.

3. Address of Operator

4006 Beltline Road, Suite 290, Dallas, Texas 75244

4. Well Location

Unit Letter 0 : 400 Feet From The south Line and 2242 Feet From The east Line

Section 1 Township 18-S Range 38-E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3656.7 gr

7. Lease Name or Unit Agreement Name

Tomlinson

8. Well No.

1

9. Pool name or Wildcat

wildcat

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The following work was performed on the dates indicated:

10-26-93: Rigged up. Set cast iron bridge plug at 6000'. 5 sx cement.

10-26-93: Set cast iron bridge plug 4950. 5 sx cement.

10-27-93: Set cast iron bridge plug at 4000. Circulated clean with salt gel.  
Spotted 25 sx cement. Cut casing 3000'.

10-28-93: Spotted 35 sx cement 3050'. Tagged 2945' Circulated hole with salt  
gel. Spotted 40 sx cement 2100' @ 8-5/8" shoe.

10-29-93: Tagged @ 1959'. At 350' set 25 sx cement.

11-1-93: Set 10 sx at surface.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Jan A. DeVault

TITLE agent

DATE 13 January 1994

(915) 694-6059

TYPE OR PRINT NAME

Jan A. DeVault

TELEPHONE NO.

(This space for State Use)

APPROVED BY

Charlie Perrin

TITLE

OIL & GAS INSPECTOR

DATE

FEB 14 1994

CONDITIONS OF APPROVAL, IF ANY: