Submit 3 Copies to Appropriate District Office

State of New Mexico erals and Natural Resources Department Energy,

Form C-103 Revised 1-1-89

... DATE -

Distance Crimes		
DISTRICT I		
P.O. Boy 1980	Hobbs, NM	8824

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

OIL

CONSERVATION DIVISION P.O. Box 2088 Santa Fe, New Mexico 87504-2088	WELL API NO. 30-025-31966 5. Indicate Type of Lease STATE XX FEE	
	6. State Oil & Gas Lease No.	
	E-7653	

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	6. State Oil & Gas Lease No. E-7653		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	7. Lease Name or Unit Agreement Name		
1. Type of Well: OIL GAS WELL X WELL OTHER	Nowata AGR State		
2. Name of Operator YATES PETROLEUM CORPORATION	8. Well No. · 2		
3. Address of Operator 105 South 4th St., Artesia, NM 88210	9. Pool name or Wildcat South Vacuum Wolfcamp		
4. Well Location Unit Letter I: 1650 Feet From The South Line and 33	Feet From The East Line		
Section 9 Township 18S Range 35E	NMPM Lea County		
3921' GR			
11. Check Appropriate Box to Indicate Nature of Notice NOTICE OF INTENTION TO:	Report, or Other Data UBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING		
	COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT		
POLEOTERICATION	CASING TEST AND CEMENT JOB		
omen.	& surface casing X		
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, work) SEE RULE 1103.	including estimated date of starting any proposed		
Spudded a 26" hole at 3:30 PM 5-7-93. Set 40' of 20" co Resumed drilling a 17-1/2" hole with rotary tools at 9:0	nductor pipe. Cemented to surface 0 PM 5-11-93.		
Ran 12 joints of 13-3/8" 54.5# J-55 ST&C R-3 (463.40') of Pattern notched guide shoe set at 450'. Insert float set sacks "H" Thixset, 5#/sack gilsonite and 1/2#/sack cellor Tailed in with 400 sacks Class "C" 2% CaCl2 (yield 1.32, 5-12-93. Bumped plug to 700 psi, OK. Circulated 96 sack Drilled out at 3:45 AM 5-13-93. Nippled up and tested to Reduced hole to 12-1/4". Resumed drilling.	seal (yield 1.43, weight 15.6). weight 14.8). PD 10:45 AM ks cement to pit. WOC 18 hours.		
I hereby contifu that the information above is true and complete to the best of my knowledge and belief.			

I hereby certify that the information above is true and complete to the best of my knowleds	ge and belief. TITLE Production Clerk	DATE May 26, 1993
TYPEOR PRINT NAME Rusty Klein		TELEPHONE NO. 505/748-1471
(This space for State Use) ORIGINAL SIGNED BY JERRY SEXTON DISTRICT I SUI ERVISOR	TING	JUN - 1 1993

_ TITLE -

APPROVED BY-CONDITIONS OF APPROVAL, IF ANY: