

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy 1430	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2820	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 2923	T. Devonian	T. Menefee	T. Madison
T. Queen 3698	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 4063	T. Montoya	T. Mancos	T. McCracken
T. San Andres 4242	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta 5910	T. McKee	Base Greenhorn	T. Granite
T. Paddock 6027	T. Ellenburger	T. Dakota	T.
T. Blinebry 6508	T. Gr. Wash	T. Morrison	T.
T. Tubb 7557	T. Delaware Sand	T. Todilto	T.
T. Drinkard 7616	T. Bone Springs	T. Entrada	T.
T. Abo 8068	T.	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....	7616	to.....	7693	No. 3, from.....	7795	to.....	7911
No. 2, from.....	7693	to.....	7795	No. 4, from.....	7911	to.....	8068

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.....
 No. 2, from to feet.....
 No. 3, from to feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology
SURF	1462	1462	RED BEDS
2863	3781	918	CARBONATES & SAND
4090	4375	285	SAND
6051	6440	389	SAND

From	To	Thickness in Feet	Lithology
1462	2863	1401	ANHYDRITE & SALT
3781	4090	309	SAND & CARBONATES
4375	6051	1676	DOLOMITE
6440	8200	1760	95/100% DOLOMITE 0/5% SAND SHALE & LIME STONE