State of New Mexico Form C-103 Submit 3 Copies Energy, Minerals and Natural Resources Department to Appropriate District Office **Revised 1-1-89** OIL CONSERVATION DIVISION DISTRICT I P.O. Box 1980, Hobbs, NM 88240 WELL API NO. P.O. Box 2088 30-025-31969 Santa Fe, New Mexico 87504-2088 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 5. Indicate Type of Lease STATE FEE L DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. B-1113 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" WARN ST A/C 2 (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: MET [AFT X OTHER 2. Name of Operator 8. Well No. Marathon Oil Company 9. Pool name or Wildcat 3. Address of Operator P.O. Box 552 Midland, Tx. 79702 **VACUUM** Well Location Unit Letter C : 1109 Feet From The NORTH 1993 Feet From The WEST Line and ownship 18-S Range 35-E

10. Elevation (Show whether DF, RKB, RT, GR, etc.) NMPM LEA County Township 18-S Section 6 3975'-GL: 3988'-KB Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK **ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB PULL OR ALTER CASING OTHER: OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. DRILLED 7 7/8" HOLE TO 8160'. TD @ 01:30 HRS 7/8-93. LOGGED WELL, RAN LSS/GR/CAL 8155'-2824' CALIPER TO SURFACE. RAN DLL 8155'-7500'. RAN 27 JTS, 5 1/2", 17#, K-55 LTC & 164 JTS, 5 1/2", 15.5#, K-55 LTC. SHOE @ 8158', FLOAT COLLAR @ 8069', STAGE TOOL @ 5691'. MIXED & PUMPED 1ST STAGE; 580 SX CLASS "H" (YIELD 1.19 C7/SK, WT. 15.6#) DROPPED BOMB & OPENED DV TOOL. CIRC 124 SX TO PIT. CIRCULATED 4 HRS. MIXED AND PUMPED 2ND STAGE LEAD SLURRY; 930 SX PACESETTER LITE "H" (YIELD 1.84, WT 12.6#) TAILED IN W/ 50 SX CLASS "C" NEAT. (YIELD 1.32 C7/SK, WT-14.8#). DROPPED PLUG & DISPLACED CMT. LOST RETURNS DURING DISPLACEMENT. DID NOT CIRCULATE CEMENT, EST TOC @ 1050'. ND BOP, SET SLIPS & CUT 5 1/2" CSG. NU 7 1/ 16" 3M TBG HEAD & TESTED SEALS TO 2000#. RELEASED RIG @ 07:00 HRS 7-12-93 I haraby certify that the information above is true and complete to the best of my knowledge and belief. ADVANCED DRILLING ENGINEER _ DATE 7-19-93 SECURATIONS.

THE OR PRINT HAME C. E. YOUNG

THE SPACE FOR State Use)

Orig. Signed by Paul Kauter
Geologist Title

JUL 23 1993

CONDITIONS OF APPROVAL, IF ANY: