Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240 OIL CONSERVATIO P.O. Box 208	8 30-025-31992
DISTRICT II P.O. Drawer DD, Artesia, NM 88210 Santa Fe, New Mexico	5. Indicate Type of Lease STATE X FEE
DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410	6. State Oil & Gas Lease No. B-1733
SUNDRY NOTICES AND REPORTS ON WEL (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN DIFFERENT RESERVOIR. USE "APPLICATION FOR PE (FORM C-101) FOR SUCH PROPOSALS.)	OR PLUG BACK TO A 7 Lease Name or Linit Agreement Name
OEL X GAS WELL OTHER	
2. Name of Operator TEXACO EXPLORATION AND PRODUCTION INC.	8. Well No. 12
3. Address of Operator P. O. Box 3109 Midland, Texas 79702	9. Pool name or Wildcat VACUUM DRINKARD
4. Well Location Unit Letter _H :1880	
Section 1 Township 18-SOUTH Range 34-EAST NMPM LEA County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR-3983', KB-3997' Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS	COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT
PULL OR ALTER CASING	CASING TEST AND CEMENT JOB
OTHER:	OTHER: PRODUCTION CASING X
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 1. DRILLED 7 7/8 HOLE TO 8000'. TD @ 7:30 AM 08-08-93. 2. HLS ATTEMPTED TO LOG - COULD NOT GET TOOL PAST 6100'. RIG DOWN HLS AND TIH. 3. RAN 43 JOINTS OF 5 1/2, 17# WC-50 AND 146 JOINTS OF 15.5#, LTC CASING SET @ 8000'. D.V. TOOL @ 5022'. 4. DOWELL CEMENTED: 1ST STAGE - 300 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 PPG, 1.94 CF/S). F/B 225 SACKS CLASS H (15.6 PPG, 1.18 CF/S). OPEN DV TOOL @ 5:30 PM 08-09-93. CIRCULATED 29 SACKS. 2ND STAGE - 1300 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 PPG, 1.94 CF/S). F/B 100 SACKS CLASS H (15.6 PPG, 1.18 CF/S). PLUG DOWN @ 1:15 AM 08-10-93. DID NOT CIRCULATE CEMENT. 5. RAN TEMPERATURE SURVEY. TOP OF CEMENT @ 1800'. 6. ND. RELEASE RIG @ 5:00 AM 08-10-93. 7. PREP TO COMPLETE.	
I hereby certify that the information above is true and complete to the best of my knowledge and SIGNATURE C.P. BASHAM TYPE OR PRINT NAME C.P. BASHAM	DRILLING OPERATIONS MANAGER DATE 08-11-93 TELEPHONE NO. 915-6884620
(This space for State Use) ORIGINAL SIGNED BY JERRY SEXTON DISTRICT I SUPERVISOR APPROVED BY CONDITIONS OF APPROVAL, IF ÁNY:	DATE AUG 13 1993