Submit 3 Copies to Appropriate District Office

State of New Mexico

Form C-103

Energy, Minerals and Natural Resources Department Revised 1-1-89 OIL CONSERVATION DIVISION DISTRICT I WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 30-025-32018 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 Santa Fe, New Mexico 87504-2088 5. Indicate Type of Lease STATE X FEE DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. B-1306 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" NEW MEXICO 'R' STATE NCT-1 (FORM C-101) FOR SUCH PROPOSALS.) Type of Well: GAS X WELL OTHER 2. Name of Operator 8. Well No. TEXACO EXPLORATION AND PRODUCTION INC. 14 3. Address of Operator 9. Pool name or Wildcat P. O. Box 3109 Midland, Texas 79702 VACUUM DRINKARD Well Location Unit Letter B : 860 Feet From The NORTH 2000 Feet From The EAST Line and Township 18-SOUTH Range 35-EAST NMPM LEA County Section 6 10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR-3975', KB-3989' Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON **ALTERING CASING** REMEDIAL WORK PLUG AND ABANDONMENT COMMENCE DRILLING OPNS. TEMPORARILY ABANDON **CHANGE PLANS** CASING TEST AND CEMENT JOB **PULL OR ALTER CASING** OTHER: SPUD & SURFACE CASING OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 1. TMBR/SHARP RIG #17 SPUD 11 INCH HOLE @ 4:15 PM 08-10-93. DRILLED TO 1455'. TD @ 2:45 AM 08-11-93. 2. RAN 33 JTS OF 8 5/8, 24#, WC-50, STC CASING SET @ 1455'. RAN 10 CENTRALIZERS. 3. DOWELL CEMENTED WITH 500 SACKS CLASS C W/ 4% GEL, 2% CACL2 (13.5 PPG, 1.74 CF/S). F/B 150 SACKS CLASS C W/ 2% CACL2 (14.8 PPG, 1.32 CF/S). PLUG DOWN @ 12:30 PM 08-11-93. CIRCULATED 170 SACKS. 4. NU BOP & TESTED TO 1500#. TESTED CASING TO 1500# FOR 30 MINUTES FROM 9:30 PM TO 10:00 PM 08-11-93. 5. WOC TIME 9 HOURS FROM 12:30 PM TO 9:30 PM 08-11-93. REQUIREMENTS OF RULE 107, OPTION 2: 1. VOLUME OF CEMENT SLURRY: LEAD 870 (CU.FT), TAIL 198 (CU.FT). 2. APPROX. TEMPERATURE OF SLURRY WHEN MIXED: 50 F. 3. EST. FORMATION TEMPERATURE IN ZONE OF INTEREST: 90 F. 4. EST. CEMENT STRENGTH AT TIME OF CASING TEST: 1120 PSI. 5. ACTUAL TIME CEMENT IN PLACE PRIOR TO TESTING: 9 HOURS. 6. DRILLING 7 7/8 INCH HOLE. I hereby certify that the information above is true and complete to the best of my knowledge and belief. DRILLING OPERATIONS MANAGER DATE 08-18-93

(This space for State Use) ORIGINAL SIGNED BY JERRY SEXTON DISTRICT I SUPERVISOR

PATAUG 2 0 1993 _ TILE -

TELEPHONE NO. 915-6884620

APPROVED BY -

TYPE OR PRINT NAME C.P. BASHAM

July 5, 1993

DATE OF TEST: 05-jul-1993

CUSTOMER

: TEXACO

FIELD

: LEA NM

WELL

: NMS RST 13, #/4

MIX WATER

Density: 8.32 lb/gal Volume: 6.32 gal/sk

Type: LO

Total liquid: 6.32 gal/sk

ADDITIVES			
Code	Concent.	Unit	
S001	2.000	% BWOC	

Rheological model (Dial 1): Bingham Plastic

 $T_y: 36.470 \ lbf/100 ft^2$

 $P_v: 12.051 \ cP$

Correlation coefficient: 0.990

Thickening Time: 1 hr50 mn to 70 BC

API Schedule: 1G1

Set condition:

Consistometer serial number:

No Fluid Loss data available

No Free Water data available

TEST NUMBER: NPD331500002

CEMENT

Class: C

Blend:

Brand: LONESTAR Plant: MARYNEAL TX

SLURRY

Density: 14.80 lb/gal

Yield: 1.32 ft³/sk

B.H.S.T.: 90.0 F B.H.C.T.: 85.0 F

Rheometer type: Fann 35

Spring factor: 1.0

Bob No: 1 Rotor No: 1

Rheological data			
Temp. (F):	80.0	0.0	
R.P.M.	Dial 1	Dial 2	
300.0	48.0	0.0	
200.0	45.0	0.0	
100.0	40.0	0.0	
60.0	36.0	0.0	
30.0	31.0	0.0	
6.0	25.0	0.0	
3.0	14.0	0.0	
0.0	0.0	0.0	
0.0	0.0	0.0	
10 minutes Gel: 0.0			

Compressive strength			
PSI	Hours	Temp. (F)	
1000	8.0	90.0	
1700	12.0	90.0	
2000	24.0	90.0	

Comment:

C + 2% 31

TAIL PIELD BLEND

LOCATION WATER USED

TVD-1460 HOBBS LAB