

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-32026
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-1306-1
7. Lease Name or Unit Agreement Name VACUUM GRAYBURG SAN ANDRES UNIT
8. Well No. 126
9. Pool name or Wildcat VACUUM GRAYBURG SAN ANDRES
10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR-3995', KB-4008'

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator TEXACO EXPLORATION AND PRODUCTION INC.
3. Address of Operator P. O. Box 3109 Midland, Texas 79702	4. Well Location Unit Letter L : 1980 Feet From The SOUTH Line and 1308 Feet From The WEST Line Section 1 Township 18-SOUTH Range 34-EAST NMPM LEA County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR-3995', KB-4008'	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER: <input type="checkbox"/>
OTHER: <input type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. DRILLED 7 7/8 HOLE TO 4900'. TD @ 4:00 AM 07-23-93.
2. HLS RAN GR-DLL-MSFL, GR-DSN-CAL-FDC FROM 4900' TO 3900'. PULLED GR-DSN TO SURFACE.
3. RAN 111 JOINTS OF 5 1/2, 15.5# J-55, LTC CASING SET @ 4900'.
4. DOWELL CEMENTED WITH 1100 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 PPG, 1.94 CF/S). F/B 200 SACKS CLASS H (15.6 PPG, 1.18 CF/S). PLUG DOWN @ 5:30 AM 07-24-93. CIRCULATED 71 SACKS.
5. ND. RELEASE RIG @ 10:00 AM 07-24-93.
6. PREP TO COMPLETE.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE C.P. Basham / SDH TITLE DRILLING OPERATIONS MANAGER DATE 07-26-93
TYPE OR PRINT NAME C.P. BASHAM TELEPHONE NO. 915-6884620

(This space for State Use)

APPROVED BY Paul Kautz TITLE Geologist DATE JUL 28 1993
CONDITIONS OF APPROVAL, IF ANY: