

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

IL CONSERVATION DIVISIC
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78
API # 30-025-32297

5a. Indicate Type of Lease State <input type="checkbox"/> For <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No. N/A

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Primero Operating, Inc.
3. Address of Operator P. O. Box 1433, Roswell, NM 88202
4. Location of Well UNIT LETTER <u>L</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>890</u> FEET FROM THE <u>West</u> LINE, SECTION <u>19</u> TOWNSHIP <u>18S</u> RANGE <u>38E</u> NMPM.

7. Unit Agreement Name
8. Farm or Lease Name Quarry
9. Well No. 1
10. Field and Pool, or Wildcat Bowers, 7 Rivers
12. County Lea

15. Elevation (Show whether DF, RT, GR, etc.)
3663 GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

Drilled 7 7/8" hole to 3206'. Core from 3206' to 3280'. Ream hole and drill 7 7/8" hole to 3320'. Log well with Sonic, CNL-FDC, and DLL-MSFL logs. RIH with 93 jts USED 5 1/2" 15.5# and 17# K-55 casing with guide shoe, float collar and five (5) centralizers. Land casing @ 3320'. Cement casing with 400 sx Halliburton Lite with 10# salt/sx and 150 sx Premium Plus with 5# KCl and 5/10 # Halad 9/sx. Plug down @ 7:00 AM 11/24/93.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Phelps White TITLE President DATE 11/29/93

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE DEC 01 1993

CONDITIONS OF APPROVAL, IF ANY: