

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. OIL CONS. COMMISSION
P.O. BOX 1980
HOBBS, NEW MEXICO

FORM APPROVED
Budget Bureau No. 1004-0135
88240 Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Southwest Royalties, Inc.

3. Address and Telephone No.

P.O. Box 11390, Midland, Texas 79702 (915) 686-9927

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FNL and 990' FWL Sec. 34, T-17-S, R-33-E

5. Lease Designation and Serial No.

NM - 801

6. If Indian, Allottee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

N/A

8. Well Name and No.

Wyatt Phillips Federal #15

9. API Well No.

30-025-32417

10. Field and Pool, or Exploratory Area

Maljamar

11. County or Parish, State

Lea, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Perf, Squeeze & Acidize

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*


6-2-94: Set 5-1/2" CIBP @ 4702', test. Pump 200 sx Class "C" neat; squeeze 4671 - 4687'. Reverse out cement, pressure to 1500 # - Held OK.

6-7-94: Circulate hole w/2% KCL water, perforate 4584 - 4635' (20 holes). Set retrievable bridge plug @ 4661'. Set packer and test to 2000 #, Held OK.

6-8-94: Spot 250 gals 15% NEFE acid across perfs. Acidize perfs 4584 - 4635' w/2000 gals 15% NEFE acid.

14. I hereby certify that the foregoing is true and correct

Signed



Title Regulatory Agent

Date

6-14-94

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date