

ATTACHMENT  
STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT  
OIL CONSERVATION DIVISION  
FORM C-105

SEELY OIL COMPANY  
CENTRAL EK QUEEN UNIT TRACT 11 WELL NO. 2  
NE/4 NE/4 SECTION 17, T18S, R34E  
LEA COUNTY, NEW MEXICO

23. CASING RECORD 8-20-94

8-5/8" OD, 23# Surface Casing cemented with  
670 sacks Halliburton Lite with 1/4# Flocele  
per sack followed with 200 sacks Premium  
Plus with 2% CaCl around shoe joint. Plug  
down 7:30 AM 08/20/94.

TOC  
@ surf

4-1/2" OD, 10.5# Production Casing cemented  
with 300 sacks Halliburton Lite with 9# salt  
per sack followed with 300 sacks Premium  
Pozmix with 6# salt per sack and 1% CFR-3.  
Plug down 7:35 AM 08/25/94.

TOC  
2912' CBL

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

08/29/94 4456'--4474' RKB Acidized with 1500 Gals.  
15% MCA utilizing ball  
sealers to ball out.

08/29/94 4456'--4474' RKB Fracture treated with  
17,600 gals Gelled Water  
carrying 16,100# 20/40  
sand and 3,000# 12/20  
sand.

per Drilled 9-26-97  
Henderson & follow  
bond log