

Form 360-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

Oil Gas
☒ Well ☐ Well ☐ Other

2. Name of Operator

Yates Drilling Company

3. Address and Telephone No.

105 South 4th Street, Artesia, NM 88210 (505-748-1471)

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 660' FWL Section 30-19S-32E

5. Lease Designation and Serial No.

NM-0107697

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Gecko Federal #1

9. API Well No.

30-025-32678

10. Field and Pool, or Exploratory Area

West Lusk Delaware

11. County or Parish, State

Lea County, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Intermediate Csg.

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well completion or Recompletion Report and Log Form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-19-94 Ran 103 jts. casing as follows: 4 jts. 8 5/8", 32# HC-80, ST&C and 99 jts. 8 5/8", 32# J-55, ST&C casing, set at 4262'. DV tool set at 2587'. Float collar set at 4262'. Cemented as follows: Stage 1: Cemented with 550 sxs. Halliburton Lite, 5#/sx Gilsonite, 1/4# sx Flocele + 2% CaCl. Tailed in with 200 sxs. Class "C", 1/4#/sx Flocele + 2% CaCl. PD at 3:15 AM, 10-20-94. Circ. 160 sxs. off DV tool.
Second Stage: Cemented with 1300 sxs. Halliburton Lite, 12#/sx Salt and 1/4#/sx Flocele. Tailed in with 200 sxs. Class "C" + 1/4#/sx. Flocele + 2% CaCl. Circulated trace of cement. WOC for 15.5 hrs. Tested BOP and resumed drilling. Notified BLM in Hobbs of cement jobs but they did not witness.

14. I hereby certify that the foregoing is true and correct

Signed

Karen J. Luskman

Title Production Clerk

Date 11-3-94

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side