

District I
PO Box 1980, Hobbs, NM 88241-1980
District II
PO Drawer DD, Artesia, NM 88211-0719
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form C-101
Revised February 10, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

¹ Operator Name and Address. SOUTHWEST ROYALTIES INC. P. O. BOX 11390 MIDLAND, TEXAS 79702		² OGRID Number 21355 ³ API Number 30-025-32E-78
⁴ Property Code 15709	⁵ Property Name CONOCO STATE "29"	⁶ Well No. 1

⁷ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the 1980'	North/South line	Feet from the 1980'	East/West line	County
J	29	18S	37E			SOUTH		EAST	LEA

⁸ Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
⁹ Proposed Pool 1 22800 E. Monument Valley SR-62					¹⁰ Proposed Pool 2				

¹¹ Work Type Code N	¹² Well Type Code O	¹³ Cable/Rotary R	¹⁴ Lease Type Code S	¹⁵ Ground Level Elevation 3723
¹⁶ Multiple NO	¹⁷ Proposed Depth 5000 4520	¹⁸ Formation SAN-ANDRES Green	¹⁹ Contractor -	²⁰ Spud Date 10/05/94

²¹ Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
12 1/4	8 5/8	24	1650	850	CIRCULATE
7 7/8	5 1/2	15.5	4850	400	

²² Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

1. Drill 12 1/4 hole to 1650'±. Run 1650± of 8 5/8" 24# J-55 ST&C Casing. Cement with 650 Sx Class "C" + 4% Gel +2% CaCl, Tail in with 200 Sx Class "C" + 2%CaCl. Circulate cement to surface.
2. Drill 7 7/8" hole to 4800'± Run 4800' of 5 1/2" 15.5# J-55 ST&C Casing. Cement with 200 Sx 50/50 POZ + additives Tail in with 200 Sx Class "C" + additives.

²³ I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature: *Joe T. Janica*
Printed name: Joe T. Janica
Title: Agent
Date: 09/23/94
Phone: -505-392-2112

OIL CONSERVATION DIVISION

Approved by: _____
Title: _____
Approval Date: SEP 26 1994 Expiration Date: _____
Conditions of Approval: Attached ☐