

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. <b>36-025-32733</b>
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Lease Name or Unit Agreement Name  Corbin "35" State
2. Name of Operator Olsen Energy, Inc.	
3. Address of Operator 16414 San Pedro, San Antonio, Texas 78232	8. Well No. 2
4. Well Location Unit Letter <u>E</u> : <u>1650</u> Feet From The <u>North</u> Line and <u>990</u> Feet From The <u>West</u> Line Section <u>35</u> Township <u>17-S</u> Range <u>33-E</u> NMPM <u>Lea</u> County <u></u>	9. Pool name or Wildcat Maljamar (GB-SA) 43329
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4128 GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
<b>NOTICE OF INTENTION TO:</b>	<b>SUBSEQUENT REPORT OF:</b>
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud 8 PM 12-6-94. Drill 12½" hole to 1506'. Set 8-5/8" 24# J-55 casing at 1506'. Cement w/485 sxs Pacesetter Lite w/6% gel, 1/4# cello-seal and 2% CaCl<sub>2</sub> followed by 200 sxs Class "C" w/2% CaCl<sub>2</sub>. Circ 125 sxs. PD 4 PM 12-8-94. WOC 12 hours. Test casing to 600#. Drill 7-7/8" hole to 4680'. Run logs. Set 5½" 17# K-55 LT&C casing at 4679'. Cement w/600 sxs of Pacesetter Lite "C" w/1.0% CaCl<sub>2</sub> followed by 185 sxs Class "C" w/5# per sack CSE + 0.5% CF-14. PD at 3:30 AM 12-17-94. Circ 94 sxs. Test casing to 1500#.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Dick Morton TITLE Drilling & Production Mgr. DATE 12-19-94

TYPE OR PRINT NAME Dick Morton TELEPHONE NO. 210-496-2466

(This space for State Use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: