## State of New Mexico

Submit 3 copies to Appropriate District Office

Ener:

linerals and Natural Resources Department

Form C-103 Revised 1-1-89

**DISTRICT I** P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

<u>D</u>

## OIL CONSERVATION DIVISION

ER	VA	TION	DIVISION	WELL API NO
	_	0000		

P.O. Box 2088 Santa Fe. New Mexico 87504-2088

	3D-025-3279
5	Indicate Type of League

SUBSEQUENT REPORT OF:

O. Box Drawer DD, Artesia, NM 88210	Salita Fe, New Mexico 07304-2000	STATE FEE
000 Rio Brazos Rd., Aztec, NM 87410		6. State Oil / Gas Lease No.
(DO NOT USE THIS FORM FOR PROPOSAL DIFFERENT RESERVOIR.	AND REPORTS ON WELL S TO DRILL OR TO DEEPEN OR PLUG BACK TO A USE "APPLICATION FOR PERMIT FOR SUCH PROPOSALS.)	7. Lease Name or Unit Agreement Name CENTRAL VACUUM UNIT
. Type of Well: OIL GAS WELL WELL	OTHER	
. Name of Operator TEXACO EXPLORA	TION & PRODUCTION INC.	8. Well No. 197
. Address of Operator P.O. Box 46510, De	nver Colorado 80201-6510	9. Pool Name or Wildcat
Well Location Unit Letter D : 717  Section 6 Town		Feet From TheLine  #PMLEACOUNTY
10. E	Elevation (Show whether DF, RKB, RT,GR, etc.)	

NOTICE OF INTENTION TO: PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PERFORM REMEDIAL WORK PLUG AND ABANDONMENT COMMENCE DRILLING OPERATION **CHANGE PLANS** TEMPORARILY ABANDON CASING TEST AND CEMENT JOB **PULL OR ALTER CASING** П SPUD, SURF CSG, PROD CSG OTHER: OTHER:

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

- 1. NABORS RIG #403 SPUD 11 INCH HOLE @ 4:00 AM 02-02-95. DRILLED TO 1187'. TD @ 2:15 AM 02-03-95.
- RAN 37 JOINTS OF 8-5/8, 24#, WC-50, STC CASING SET @ 1570'. RAN 12 CENTRALIZERS.
- DOWELL CEMENTED WITH 500 SACKS CLASS C W/ 4% GEL, 2% CACL2 (13.5 PPG, 1.74 CF/S). F/B 150 SACKS CLASS C W/ 2% CACL2 (14.8 PPG, 1.34 CF/S). PLUG DOWN @ 1:45 PM 02-03-95. CIRCULATED 200 SACKS.
- NU BOP & TESTED TO 3000#. TESTED CASING TO 1000# FOR 30 MINUTES FROM 10:00 PM TO 10:30 PM 02-04-95.
- WOC TIME 32.25 HOURS FROM 1:45 PM 02-03-95 TO 10:00 PM 02-05-95.
- DRILLING 7-7/8 HOLE. 6.
- DRILLED 7-7/8 HOLE TO 4850'. TD @ 12:30 AM 02-09-95.
- HLS RAN DLL-MSFL-SDDS NEUTRON-GR-CAL.COMPUTER LOG FROM 3900' TO 4850'. 8.
- RAN 115 JOINTS OF 5-1/2, 15.5# WC-50, LTC CASING SET @ 4850'.
- DOWELL CEMENTED WITH 775 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 PPG, 1.94 CF/S). F/B 200 SACKS 50/50 POZ CLASS H W/ 2% GEL, 5% SALT, 1/4# FLOCELE (14.2 PPG, 1.35 CF/S), PLUG DOWN @ 6:30 AM 02-10-95, CIRCULATED 150 SACKS.
- 11. ND. RELEASE RIG @ 10:00 AM 02-10-95.
- 12. PREP TO COMPLETE.

hereby certify that the information above is true and complete to the best of my knowledge and beief.									
• •	Basham SRH I		Drilling Operations Mgr.	DATE	2/15/95				
TYPE OR PRINT NAME	C. P. Basham			Telephone No.	(303)621-4851				
(This space for State Use)	Orig. Signed by Faul Kautz			FER	9 1 1005				
APPROVED BY	Goologiat TI	ITLE_		DATE_1 LD	2 1 1995				
CONDITIONS OF APPROVAL,	DeSofreRichola 10-04 var 2 0								

<sup>12.</sup> Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.