State of New Mexico

Submit 3 copies to Appropriate District Office

. Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

FEE [

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

OIL CONSERVATION DIVISION

Box 2088	30-25-32792

Santa Fe, New Mexico 87504-2088 Indicate Type of Lease

STATE |

WELL API NO

6. State Oil / Gas Lease No. 1000 Rio Brazos Rd., Aztec, NM 87410 SUNDRY NOTICES AND REPORTS ON WELL (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.) CENTRAL VACUUM UNIT OIL 1. Type of Well: WELL WELL **OTHER** 2. Name of Operator 8. Well No. **TEXACO EXPLORATION & PRODUCTION INC.** 204 3. Address of Operator 9. Pool Name or Wildcat P.O. Box 46510, Denver Colorado 80201-6510 4. Well Location

Feet From The WEST 1994 Feet From The NORTH Line and 1073

Section 6 Township 18-S Range 35-E NMPM LEA COUNTY

10. Elevation (Show whether DF, RKB, RT,GR, etc.) 3969

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK		PLUG AND ABANDON		REMEDIAL WORK	ALTERING CASING	
TEMPORARILY ABANDON		CHANGE PLANS		COMMENCE DRILLING OPERATION	PLUG AND ABANDONMENT	
PULL OR ALTER CASING				CASING TEST AND CEMENT JOB		
OTHER:				OTHER: SPUD, SUR	CSG,PROD CSG	

- NABORS #404 SPUD 11 INCH HOLE @ 7:00 AM 02-05-95. DRILLED TO 1050'. TD @ 1:30 AM 02-06-95.
- RAN 37 JOINTS OF 8-5/8, 24#, WC-50, STC CASING SET @ 1546'. RAN 12 CENTRALIZERS. 2
- 3. DOWELL CEMENTED WITH 400 SACKS CLASS C W/ 4% GEL, 2% CACL2 (13.5 PPG, 1.74 CF/S). F/B 150 SACKS CLASS C W/ 2% CACL2 (14.8 PPG, 1.34 CF/S). PLUG DOWN @ 10:15 AM 02-06-95. CIRCULATED 132 SACKS.
- NU BOP & TESTED TO 3000#. TESTED CASING TO 1000# FOR 30 MINUTES FROM 3:45 PM TO 4:15 PM 02-07-95.
- WOC TIME 29.00 HOURS FROM 10:15 AM 02-06-95 TO 3:45 PM 02-07-95.
- DRILLING 7 7/8 HOLE.
- 7 DRILLED 7 7/8 HOLE TO 4850'. TD @ 5:00 AM 02-11-95.
- HLS RAN DLL-MSFL,SDDS-NEUTRON-GR-CAL,COMPUTER LOG FROM 2700' TO 4850'.
- RAN 112 JOINTS OF 5-1/2, 15.5# WC-50, LTC CASING SET @ 4850'.

 DOWELL CEMENTED WITH 750 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 PPG, 1.94 CF/S). F/B 200 SACKS 50/50 POZ CLASS H W/ 2% GEL, 5% SALT, 1/4# FLOCELE (14.2 PPG, 1.35 CF/S). PLUG DOWN @6:30 PM 2-13-95. CIRCULATED 100 SACKS.
- ND. RELEASE RIG @ 10:30 PM 02-12-95.
- 12. PREP TO COMPLETE.

I hereby certify that the information	above is true and complete to the best of my knowledge and belief.			
SIGNATURE CO	Basham SAL TITLE	Drilling Operations Mgr.	DATE 3	/9/95
TYPE OR PRINT NAME	C. P. Basham		Telephone No.	(303)621-4851
(This space for State Use)	ORIGINAL SIGNED BY JERRY SEXTON DISTRICT I SUPERVISOR		l.:	
APPROVED BY	TITLE		DATE	· 1395
CONDITIONS OF APPRO	OVAL IF ANY:			

^{12.} Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.