

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-32871
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil / Gas Lease	B-1733

WELL COMPLETION OR RECOMPLETION REPORT AND LOG									
1a. Type of Well: OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER <u>INJECTION</u>					7. Lease Name or Unit Agreement Name NEW MEXICO 'L' STATE				
b. Type of Completion: NEW WELL ☒ WORKOVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RES. ☐ OTHER					8. Well No. 16				
2. Name of Operator TEXACO EXPLORATION & PRODUCTION INC.					9. Pool Name or Wildcat VACUUM DRINKARD				
3. Address of Operator P.O. BOX 730, HOBBS, NM 88240									
4. Well Location Unit Letter <u>A</u> : <u>1310</u> Feet From The <u>NORTH</u> Line and <u>10</u> Feet From The <u>EAST</u> Line Section <u>1</u> Township <u>18-S</u> Range <u>34-E</u> NMPM <u>LEA</u> COUNTY									
10. Date Spudded 3/31/95		11. Date T.D. Reached 4/15/95		12. Date Compl. (Ready to Prod.) 5/3/95		13. Elevations (DF & RKB, RT, GR, etc.) GL-3984'; KB-3998.8		14. Elev. Csghead 3984'	
15. Total Depth 8000'		16. Plug Back T.D. 7980'		17. If Mult. Compl. How Many Zones?		18. Intervals Drilled By		Rotary Tools 0-8000'	
19. Producing Interval(s), of this completion - Top, Bottom, Name 7496' - 7908': VACUUM DRINKARD								20. Was Directional Survey Made YES	
21. Type Electric and Other Logs Run GR-DLL-MSFL-CSL, GR-CSNG-SDL-DSN, GR-DSN								22. Was Well Cored NO	
23. CASING RECORD (Report all Strings set in well)									
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENT RECORD	
8 5/8"		24#		1525'		11"		CL-C 525 SX, CIRC 176	
5 1/2"		15.5 & 17#		8000'		7 7/8"		CL-H 1830 SX, CIRC 165	
24. LINER RECORD									
SIZE		TOP		BOTTOM		SACKS CEMENT		SCREEN	
25. TUBING RECORD									
SIZE		DEPTH SET		PACKER SET					
2 3/8"		7452'		7455'					
26. Perforation record (interval, size, and number) 7496'-7500', 16'-20', 46'-52', 58'-60', 64'-74', 7596'-7614', 7626'-42', 48'-58', 62'-66', 7670'-7700', 7706'-16', 20'-26', 36'-46', 7756'-60', 66'-90', 7800'-08', 36'-40', 46'-50', 66'-72', 83'-86', 94'-98', 7904'-08'									
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.									
DEPTH INTERVAL					AMOUNT AND KIND MATERIAL USED				
7756'-7908'					ACID - 9,000 GALS 20% HCL NEFE				
7626'-7746'					ACID - 13,000 GALS 20% HCL NEFE				
7496'-7614'					ACID - 7,000 GALS 20% HCL NEFE				
28. PRODUCTION									
Date First Production		Production Method (Flowing, gas lift, pumping - size and type pump)						Well Status (Prod. or Shut-in) SHUT-IN	
Date of Test		Hours tested		Choke Size		Prod'n For Test Period		Oil - Bbl.	
								Gas - MCF	
								Water - Bbl.	
								Gas - Oil Ratio	
Flow Tubing Press.		Casing Pressure		Calculated 24-Hour Rate		Oil - Bbl.		Gas - MCF	
								Water - Bbl.	
								Oil Gravity - API -(Corr.)	
29. Disposition of Gas (Sold, used for fuel, vented, etc.)								Test Witnessed By HOLLICE CLAY	
30. List Attachments DEVIATION SURVEY									
31. I hereby certify that the information on both sides of this form is true and complete to the best of my knowledge and belief.									
SIGNATURE <u>Monte C. Duncan</u>					TITLE <u>Engr Asst</u>		DATE <u>5/16/95</u>		
TYPE OR PRINT NAME <u>Monte C. Duncan</u>					Telephone No. <u>397-0418</u>				

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	1428'	T. Canyon
T. Salt	1548'	T. Strawn
B. Salt	2625'	T. Atoka
T. Yates	2812'	T. Miss
T. 7 Rivers	3575'	T. Devonian
T. Queen	3690'	T. Silurian
T. Grayburg	4011'	T. Montoya
T. San Andres	4241'	T. Simpson
T. Glorieta	5837'	T. McKee
T. Paddock	5990'	T. Ellenburger
T. Blinebry	6363'	T. Gr. Wash
T. Tubb	7422'	T. Delaware Sand
T. Drinkard	7540'	T. Bone Springs
T. Abo		T.
T. Wolfcamp		T.
T. Penn		T.
T. Cisco (Bough C)		T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 7756' to 7908'

No. 2, from 7626' to 7746'

No. 3, from 7496' to 7614'

No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from to feet

No. 2, from to feet

No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0'	1428'	1428'	SS, SHALE				
1428'	1548'	120'	ANHYDRITE				
1548'	2625'	1077'	SALT				
2625'	4011'	1386'	ANHYDRITE, DOLOMITE, SS				
4011'	7540'	3529'	ANHYDRITE, DOLOMITE, LIME				