

Submit 3 Copies To Appropriate District Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised March 25, 1999

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO.  
30-025-32874

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
B-1306

7. Lease Name or Unit Agreement Name:

New Mexico "R" State NCT-1

8. Well No.  
17

9. Pool name or Wildcat  
Vacuum Drinkard

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other ☒ Injector

2. Name of Operator  
Chevron Texaco Corporation

3. Address of Operator  
P.O. Box 3109 Midland, Texas 79702

4. Well Location

Unit Letter G : 2530 feet from the North line and 2530 feet from the East line

Section 6 Township 18 S Range 35 E NMPM Lea County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

1. Set 5 1/2" CIBP @ 7600 Spot 25 sxs. Plug 7600 to 7400 (Drinkard) Tag @ 7328

2. Displace hole w/MLF 9.5# Brine w/25# gel p/BBL.

3. Spot 25 sxs. Plug 3800 to 3600 (Queen)

4. Spot 25 sxs. Plug 2800 to 2600 (Yates, B-Salt) Tag @ 2525

5. Spot 50 sxs. Plug 1600 to 1200 (8 5/8 shoe, T-Salt) Tag @ 1087

6. CIRC cement 30 to surf. w/15 sxs., install dry hole marker (12/27/01)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jimmy Bagley TITLE MANAGER DATE 12/27/01

Type or print name JIMMY BAGLEY Telephone No. (915) 683-4996  
(This space for State use)

APPROVED BY Johnny Robinson TITLE COMPLIANCE OFFICER DATE APR  
Conditions of approval, if any:

COMPLIANCE OFFICER

GWW