Submit 3 Copies to Appropriate District Office

## State of New Mexico finerals and Natural Resources Department Energ

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

OIL	CONSERVATION DIVISION
	310 Old Santa Fe Trail, Room 206

WELL API NO.

310 Uld Santa re Irail, Room	1 .3(1~(1/ .1~.),3,1,1/
DISTRICT II Santa Fe, New Mexico 8759 P.O. Drawer DD, Artesia, NM 88210	5. Indicate Type of Lease
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	6. State Oil & Gas Lease No.
OUNDS AND DEPOSITO ON WIFE LO	B-2516
SUNDRY NOTICES AND REPORTS ON WELLS  ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUC  DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  (FORM C-101) FOR SUCH PROPOSALS.)	7. Lease Name or Unit Agreement Name SEMGSAU
1. Type of Well: OIL GAS WELL OTHER	SEMOSAU
2. Name of Operator Cross Timbers Operating Company	8. Well No. 614
3. Address of Operator	9. Pool name or Wildcat
P. O. Box 52070, Midland, Texas 79710  4. Well Location	Maljamar Grayburg San Andres
Unit Letter N: 1070 Feet From The South L	ne and 1888 Feet From The West Line
1 Section Township Mange	3E NMPM Lea County
10. Elevation (Show whether DF, RKB) 4,052 GR	K1, GR, etc.)
11. Check Appropriate Box to Indicate Nature	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIA	DIAL WORK ATTERING CASING
	ENCE DRILLING OPNS. X PLUG AND ABANDONMENT
PULL OR ALTER CASING CASING	TEST AND CEMENT JOB X
OTHER: OTHER	: 니
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pework) SEE RULE 1103.	rtinent dates, including estimated date of starting any proposed
MIRU Norton Drilling Co. Rig #7. Spudded well @ 4:0 Mechanical problems w/rig. Called OCD @ Hobbs, New surface csg @ 362'. Ran 8 jts new 8-5/8", 24#, J-55 Class "C" cmt w/2% CaCl. Circ 84sx to surf. NU csg Drld 7-7/8" hole to 4395'. TD hole @ 4:00 am $5/2/96$ LTC csg. Set @ 4394'. Cmt'd w/650sx 65:35 Pozmix "Class "C" cmt w/1.1% FL-62 & 0.3% CA-32. Circ 34sx slips & cut off csg. Rel rig. WOCU.	Mexico & received permission to set , STC csg. Set @ 357'. Cmt'd w/250sx head & BOP. Tstd csg & BOP to 1000 psig. . Ran 106 jts new 5-1/2", 15.50#, J&K-55, C" cmt w/6% gel & 5#/sx salt & 200sx
G. F. Ramsey, Jr.	illing Engineer DATE 5/9/96 TELEPHONE NO.
(This space for State Use)  ORIGINAL SIGNED BY  GARY WINK  FIELD REP. II  TITLE	DATE MAY 14 1996
MINO IN P.	

