

DISTRICT I

P. O. Box 1980, Hobbs, NM 88240

DISTRICT II

P. O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P. O. Box 2088
Santa Fe, NM 87504-2088

WELL API NO.

30-025-33504

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

B-2148

7. Lease Name or Unit Agreement Name

Caprock Maljamar Unit

8. Well No.

236

9. Pool name or Wildcat

Maljamar Grayburg San Andres

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

The Wiser Oil Company

3. Address of Operator

P.O. Box 2568 Hobbs, New Mexico 88241

4. Well Location

Unit Letter E : 2460 Feet From The North Line and 1308 Feet From The West Line

Section 28 Township 17S Range 33E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

4181' GL

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Perforate & Acidize ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8/23/96 Halliburton perforated San Andres Upper Jackson f/4651'-52', 79'-86', & 91'-98' w/1 SPF (18 holes).

8/26/96 Halliburton acidized San Andses Upper Jackson w/2700 gals. 15% NE-FE acid w/36 ball sealers. Formation broke at 2936#. ATP 3300# @ 3.8 bpm. MTP 3530# @ 4.5 bpm. ISIP 2909#. 5 min. 2473#. 10 min. 2209#. 15 min. 1991#.

8/27/96 Halliburton perforated San Andres Lower Vacuum f/4591'-94', 99'-4604' & 07'-09' w/1 SPF (13 holes).

8/28/96 Halliburton acidized San Andres Lower Vacuum w/2000 gals. 15% NE-FE acid w/26 ball sealers. Formation broke at 3500#. Balled out w/25 bbls acid in formation. ATP 3400# @ 3.7 bpm. MTP 4654# @ 4.5 bpm. ISIP 2623#. 5 min. 2403#. 10 min. 2352#. 15 min. 2313#.

8/29/96 Halliburton perforated San Andres upper Vacuum f/4514'-28' w/1 SPF (15 holes).

8/30/96 Halliburton acidized San Andres Upper Vacuum w/2300 gals. 15% NE-FE acid + 30 ball sealers. Formation broke at 4480#. Balled out w/23 bbls. acid in formation. ATP 3250# @ 3.5 bpm. MTP 4820# @ 4.5 bpm. ISIP 2566#. 5 min. 2461#. 10 min. 2422#. 15 min. 2396#.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Mary Jo Turner

TITLE Completion Department

Date

September 16, 1996

TYPE OR PRINT NAME

Mary Jo Turner

TELEPHONE NO. (505) 392-9797

(This space for State Use)

ORIGINAL SUBMITTED TO THE COMMISSION

DISTRICT I OFFICE

APPROVED BY

TITLE

DATE

Oct 21 1996