Submit 3 Copies to Appropriate

State of New Mexico Energy, Minerals & Natural Resources Department

Form C-103 Revised 1-1-89

	Energy, Minerals & Natural Resources Department	Revised 1-1-89
DISTRICT I	OIL CONSERVATION DIVISION	WELL API NO.
P. O. Box 1980, Hobbs, NM 88240	P. O. Box 2088	30-025-33504
DISTRICT II	Santa Fe, NM 87504-2088	5. Indicate Type of Lease STATE FEE
P. O. Drawer DD, Artesia, NM 88210	, -	
DISTRICT III		6. State Oil & Gas Lease No.
1000 Rio Brazos Rd., Aztec, NM 87410		B-2148
	TICES AND REPORTS ON WELLS	
	PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A SERVOIR, USE "APPLICATION FOR PERMIT"	7. Lease Name or Unit Agreement Name
(FOR	M C-101) FOR SUCH PROPOSALS.)	Caprock Maljamar Unit
1 Type of Well: OIL GAS		
WELL WELL	OTHER	
2. Name of Operator		8. Well No.
The Wiser C	Dil Company	236
3. Address of Operator		9. Pool name or Wildcat
	568 Hobbs, New Mexico 88241	Maljamar Grayburg San Andres
4. Well Location		
Unit Letter E :	2460 Feet From The North Line and 13	08 Feet From The West Line
Section 28		NMPM Lea County
	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4181' GL	
	heck Appropriate Box to Indicate Nature of Notice, R	anast or Other Date
		SEQUENT REPORT OF:
NOTICE OF I		DEQUENTREFURTUR.
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	LALTERING CASING
PERFORM REMEDIAL WORK TEMPORARILY ABANDON	PLUG AND ABANDON REMEDIAL WORK CHANGE PLANS COMMENCE DRILLING	LALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS COMMENCE DRILLING	ALTERING CASING PLUG AND ABANDONMENT
		ALTERING CASING OPNS. PLUG AND ABANDONMENT
TEMPORARILY ABANDON	CHANGE PLANS COMMENCE DRILLING	ALTERING CASING PLUG AND ABANDONMENT
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed O	CHANGE PLANS COMMENCE DRILLING CASING TEST AND CEI	ALTERING CASING B OPNS. PLUG AND ABANDONMENT MENT JOB
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER:	CHANGE PLANS COMMENCE DRILLING CASING TEST AND CEI OTHER:	ALTERING CASING B OPNS. PLUG AND ABANDONMENT MENT JOB
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed Owork) SEE RULE 1103.	CHANGE PLANS COMMENCE DRILLING CASING TEST AND CEI OTHER:	ALTERING CASING B OPNS. PLUG AND ABANDONMENT MENT JOB PLUG AND ABANDONMENT MENT JOB B COPNS. PLUG AND ABANDONMENT MENT JOB B COPNS. PLUG AND ABANDONMENT MENT JOB B COPNS. PLUG AND ABANDONMENT B COPNS. PLUG A
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed Owork) SEE RULE 1103. MIRU Norton Drilling C	CHANGE PLANS COMMENCE DRILLING CASING TEST AND CEI OTHER: Operations (Clearly state all pertinent details, and give pertinent data o., Rig # 5. Spudded 12-1/4" hole @ 2:45 p.m.	ALTERING CASING B OPNS. PLUG AND ABANDONMENT MENT JOB Des, including estimated date of starting any proposed 08/01/96. Drilled hole to 368'. Ran
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed Owork) SEE RULE 1103. MIRU Norton Drilling C 8 jts. 8-5/8", 23#, K-55,	CHANGE PLANS CASING TEST AND CEI OTHER: Department details, and give pertinent date o., Rig # 5. Spudded 12-1/4" hole @ 2:45 p.m. LT&C csg. Set at 365'. Halliburton cemented v	ALTERING CASING BOPNS. PLUG AND ABANDONMENT MENT JOB Des, including estimated date of starting any proposed 08/01/96. Drilled hole to 368'. Ran with 325 sx. Class "C" containing
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed Owork) SEE RULE 1103. MIRU Norton Drilling C 8 jts. 8-5/8", 23#, K-55, 1/4#/sk. Flocele + 2% Ca	CHANGE PLANS CASING TEST AND CEID OTHER: Operations (Clearly state all pertinent details, and give pertinent data on the control of the con	ALTERING CASING BOPNS. PLUG AND ABANDONMENT MENT JOB Des, including estimated date of starting any proposed 08/01/96. Drilled hole to 368'. Ran with 325 sx. Class "C" containing
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed Owork) SEE RULE 1103. MIRU Norton Drilling C 8 jts. 8-5/8", 23#, K-55,	CHANGE PLANS CASING TEST AND CEID OTHER: Operations (Clearly state all pertinent details, and give pertinent data on the control of the con	ALTERING CASING BOPNS. PLUG AND ABANDONMENT MENT JOB Des, including estimated date of starting any proposed 08/01/96. Drilled hole to 368'. Ran with 325 sx. Class "C" containing
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed Owork) SEE RULE 1103. MIRU Norton Drilling C 8 jts. 8-5/8", 23#, K-55, 1/4#/sk. Flocele + 2% Cacsg. to 1000# for 30 min	CHANGE PLANS CASING TEST AND CEID OTHER: Department details, and give pertinent data co., Rig # 5. Spudded 12-1/4" hole @ 2:45 p.m. LT&C csg. Set at 365'. Halliburton cemented values, no pressure loss.	ALTERING CASING PLUG AND ABANDONMENT PLUG ABANDONMENT PLUG AND ABANDONMENT PLUG AND ABANDONMENT PLUG AND
PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed Owork) SEE RULE 1103. MIRU Norton Drilling C 8 jts. 8-5/8", 23#, K-55, 1/4#/sk. Flocele + 2% Cacsg. to 1000# for 30 min	CHANGE PLANS CASING TEST AND CEID OTHER: Operations (Clearly state all pertinent details, and give pertinent data on the control of the con	ALTERING CASING PLUG AND ABANDONMENT PLUG AB
PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed Owork) SEE RULE 1103. MIRU Norton Drilling C 8 jts. 8-5/8", 23#, K-55, 1/4#/sk. Flocele + 2% Cacsg. to 1000# for 30 mir Drilled 7-7/8" production 17#, K-55, LT&C csg.	CHANGE PLANS CASING TEST AND CEID OTHER: Department details, and give pertinent data co., Rig # 5. Spudded 12-1/4" hole @ 2:45 p.m. LT&C csg. Set at 365'. Halliburton cemented van Cl. Plug down @ 9:00 p.m. 08/01/96. Circulate nutes, no pressure loss. In hole to a depth of 4900'. Ran logs and elected Set at 4900'. Halliburton cemented w/1000 gals	ALTERING CASING PLUG AND ABANDONMENT PLUG ABANDONMENT PLUG AND ABANDONMENT PLUG AND ABANDONMENT PLUG AND
PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed Owork) SEE RULE 1103. MIRU Norton Drilling C 8 jts. 8-5/8", 23#, K-55, 1/4#/sk. Flocele + 2% Cacsg. to 1000# for 30 min Drilled 7-7/8" production 17#, K-55, LT&C csg. Lite with 8# salt/sk + 1/4	CHANGE PLANS CASING TEST AND CEID OTHER: OTH	ALTERING CASING PLUG AND ABANDONMENT PRINT JOB PRINT
PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed Owork) SEE RULE 1103. MIRU Norton Drilling C 8 jts. 8-5/8", 23#, K-55, 1/4#/sk. Flocele + 2% Cacsg. to 1000# for 30 min Drilled 7-7/8" productio 17#, K-55, LT&C csg. Lite with 8# salt/sk + 1/4 1/4# flocele/sk. Displace	CHANGE PLANS CASING TEST AND CEID OTHER: Operations (Clearly state all pertinent details, and give pertinent data on the control of the con	ALTERING CASING PLUG AND ABANDONMENT PRINT JOB PRINT
PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed Owork) SEE RULE 1103. MIRU Norton Drilling C 8 jts. 8-5/8", 23#, K-55, 1/4#/sk. Flocele + 2% Cacsg. to 1000# for 30 mir Drilled 7-7/8" production 17#, K-55, LT&C csg. Lite with 8# salt/sk + 1/4 1/4# flocele/sk. Displace tested casing to 1500# for	CHANGE PLANS CASING TEST AND CEID OTHER: OTH	ALTERING CASING PLUG AND ABANDONMENT PRINT JOB PRINT
PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed Owork) SEE RULE 1103. MIRU Norton Drilling C 8 jts. 8-5/8", 23#, K-55, 1/4#/sk. Flocele + 2% Cacsg. to 1000# for 30 min Drilled 7-7/8" productio 17#, K-55, LT&C csg. Lite with 8# salt/sk + 1/4 1/4# flocele/sk. Displace	CHANGE PLANS CASING TEST AND CEID OTHER: Operations (Clearly state all pertinent details, and give pertinent data on the control of the con	ALTERING CASING PLUG AND ABANDONMENT PRINT JOB PRINT
PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed Owork) SEE RULE 1103. MIRU Norton Drilling C 8 jts. 8-5/8", 23#, K-55, 1/4#/sk. Flocele + 2% Cacsg. to 1000# for 30 mir Drilled 7-7/8" production 17#, K-55, LT&C csg. Lite with 8# salt/sk + 1/4 1/4# flocele/sk. Displace tested casing to 1500# for	CHANGE PLANS CASING TEST AND CEID OTHER: Operations (Clearly state all pertinent details, and give pertinent data on the control of the con	ALTERING CASING PLUG AND ABANDONMENT PRINT JOB PRINT
PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed Owork) SEE RULE 1103. MIRU Norton Drilling C 8 jts. 8-5/8", 23#, K-55, 1/4#/sk. Flocele + 2% Cacsg. to 1000# for 30 min Drilled 7-7/8" productio 17#, K-55, LT&C csg. Lite with 8# salt/sk + 1/4 1/4# flocele/sk. Displace tested casing to 1500# for 4:00 a.m. 08/07/96.	CHANGE PLANS CASING TEST AND CEIDTHER: OTHER: Operations (Clearly state all pertinent details, and give pertinent data and	ALTERING CASING PLUG AND ABANDONMENT PRINT JOB PRINT
PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed Owork) SEE RULE 1103. MIRU Norton Drilling C 8 jts. 8-5/8", 23#, K-55, 1/4#/sk. Flocele + 2% Cacsg. to 1000# for 30 mir Drilled 7-7/8" production 17#, K-55, LT&C csg. Lite with 8# salt/sk + 1/4 1/4# flocele/sk. Displace tested casing to 1500# for 4:00 a.m. 08/07/96.	CHANGE PLANS CASING TEST AND CEIDTHER: Departions (Clearly state all pertinent details, and give pertinent data co., Rig # 5. Spudded 12-1/4" hole @ 2:45 p.m. LT&C csg. Set at 365'. Halliburton cemented vacl. Plug down @ 9:00 p.m. 08/01/96. Circulate nutes, no pressure loss. In hole to a depth of 4900'. Ran logs and elected Set at 4900'. Halliburton cemented w/1000 gals 4# flocele/sk. followed by 250 sx. Premium Plus ed w/2 bbls. FW + 12 bbls. MSA + 99 bbls. KCI for 30 minutes, no pressure loss. Plug down at 2:10 is true and complete to the best of my knowledge and belief.	ALTERING CASING PLUG AND ABANDONMENT DES. including estimated date of starting any proposed O8/01/96. Drilled hole to 368'. Ran with 325 sx. Class "C" containing ed 68 sx. cmt. NU BOP & tested to run casing. Ran 117 jts. 5-1/2", Superflush 102 + 900 sx. Halliburton with 3# KCL/sk. + .5% Halad 344 + water. Circ. 89 sx. cmt. Pressure O0 a.m. 08/07/96. Released rig at
PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed Owork) SEE RULE 1103. MIRU Norton Drilling C 8 jts. 8-5/8", 23#, K-55, 1/4#/sk. Flocele + 2% Cacsg. to 1000# for 30 mir Drilled 7-7/8" production 17#, K-55, LT&C csg. Lite with 8# salt/sk + 1/4 1/4# flocele/sk. Displace tested casing to 1500# for 4:00 a.m. 08/07/96.	CHANGE PLANS CASING TEST AND CEIDTHER: OTHER: Operations (Clearly state all pertinent details, and give pertinent data and	ALTERING CASING PLUG AND ABANDONMENT DES. including estimated date of starting any proposed O8/01/96. Drilled hole to 368'. Ran with 325 sx. Class "C" containing ed 68 sx. cmt. NU BOP & tested to run casing. Ran 117 jts. 5-1/2", Superflush 102 + 900 sx. Halliburton with 3# KCL/sk. + .5% Halad 344 + water. Circ. 89 sx. cmt. Pressure O0 a.m. 08/07/96. Released rig at

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
T. Anhy			T. Canyon	T. Ojo A	lamo		T. Penn. "B"
T. Salt			T. Strawn	T. Kirtla	nd-Fruitla	T. Penn. "C"	
B. Salt			T. Atoka		ed Cliffs_		T. Penn. "D"
T. Yates		2726'	T. Miss	T. Cliff I	louse	T. Leadville	
T. 7 River	rs	3104'	T. Devonian	T. Menel	ee	T. Madison	
Γ. Queen		3712'	T. Silurian	T. Point	Lookout_	T. Elbert	
T. Graybu	ırg	4074	T. Montoya	T. Manco	os	T. McCracken	
	ndres		T. Simpson	T. Galluj)	T. Ignacio Otzte	
	a		T. McKee	Base Gre	enhorn_	T. Granite	
Γ. Paddoc	Paddock		T. Ellenburger	T. Dakot	B		T
T. Blineb	. Blinebry		T. Gr. Wash	T. Morris	son	T	
r. Tubb_	•		T. Delaware Sand	T. Todilt	0	T	
T. Drinka	rd		T. Bone Springs	T. Entrad	T. Entrada		<u>T</u>
	Abo		T	T. Winga	ite	_ T	
T. WolfcampT.		T	T. Chinle			T	
		T	T. Perma	in		_ T	
Γ. Cisco (Bough C) T.		Т.	T. Penn '	'A"	T.		
No. 1, fromto					om	to to	
Include da	ata on rate of	water inflow	and elevation to which water ro	se in hole.			
No. 1, from to			fæt				
No. 2, from to			feet				
No. 3, fro	m		to			feet	
			LITHOLOGY RECC	RD (Attach add	litional	sheet if neces	sary)
		ickness	Lithology	From	То	Thickness	Lithology