

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
310 Old Santa Fe Trail, Room 206  
Santa Fe, New Mexico 87503

WELL API NO.
30-025-33593
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 003355

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Lease Name or Unit Agreement Name SEMGSAU
2. Name of Operator CROSS TIMBERS OPERATING COMPANY	8. Well No. 908
3. Address of Operator 3000 N. Garfield, Suite 175 Midland, Texas 79705	9. Pool name or Wildcat Maljamar Grayburg San Andres
4. Well Location Unit Letter <u>A</u> : <u>330</u> Feet From The <u>North</u> Line and <u>330</u> Feet From The <u>East</u> Line Section <u>32</u> Township <u>17S</u> Range <u>33E</u> NMPM Lea County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4,074' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-16-96 MIRU Lakota Drilling Company Rig #6. Spudded well 10-16-96.

10-17-96 Drilled 12-1/4" hole to 416'. Ran 9 jts of 8-5/8", 23#, LT-50 csg, set at 415'. Cemented casing with 275 sacks of Class "C" cement, containing 2% CaCl<sub>2</sub> (mixed at 14.8 ppg, 1.34 ft<sup>3</sup>/sk). Circ 48 sacks to pit. Plug down at 10:00 AM 10-17-96. WOC, NU BOPE, prep to drill out.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Bobby L. Smith TITLE Drilling Engineer DATE 10-28-96  
TYPE OR PRINT NAME Bobby L. Smith TELEPHONE NO. (915) 682-8873

(This space for State Use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE 10/30/96  
CONDITIONS OF APPROVAL, IF ANY: