

DISTRICT I
P. O. Box 1980, Hobbs, NM 88240

DISTRICT II
P. O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P. O. Box 2088
Santa Fe, NM 87504-2088

WELL API NO. 30-025-33723
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-2148
7. Lease Name or Unit Agreement Name Caprock Maljamar Unit
8. Well No. 281
9. Pool name or Wildcat Maljamar Grayburg San Andres
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4088'

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator The Wiser Oil Company	
3. Address of Operator P.O. Box 2568 Hobbs, New Mexico 88241	
4. Well Location Unit Letter <u>M</u> : <u>330</u> Feet From The <u>South</u> Line and <u>1210</u> Feet From The <u>West</u> Line Section <u>28</u> Township <u>17S</u> Range <u>33E</u> NMPM <u>Lea</u> County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4088'	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRU Norton Drilling Co., Rig # 5. Spudded 12-1/4" hole @ 4:00 p.m. 12/22/96. Drilled hole to 396'. Ran 8 jts. 8-5/8", 20#, ISW-42, ST&C csg. Set at 391'. Halliburton cemented with 325 sx. Class "C" containing 1/4#/sk. Flocele + 2% CaCl. Plug down @ 10:30 p.m. 12/22/96. Circulated 30 sx. cmt. NU BOP & tested csg. to 1000# for 30 minutes, no pressure loss.

Drilled 7-7/8" production hole to a depth of 4775'. Ran casing as follows: 115 jts. 5-1/2", 17#, J-55 LT&C csg. Set at 4775'. Halliburton cemented w/1000 gals. Superflush 102 + 900 sx. Halliburton Lite with 8# salt/sk + 1/4# flocele/sk. followed by 250 sx. Premium Plus with 3# KCL/sk. + .5% Halad 344 + 1/4# flocele/sk. Displaced w/1 bbl. FW + 12 bbls. MSA + 97 bbls. FW w/Lo-Surf 300. Circ. 128 sx. cmt. Pressure tested casing to 1500# for 30 minutes, no pressure loss. Plug down at 1:15 a.m. 12/30/96. Released rig at 3:15 a.m. 12/30/96.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mary Jo Turner TITLE Drilling Department DATE December 31, 1996

TYPE OR PRINT NAME Mary Jo Turner TELEPHONE NO. (505) 392-9797

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT SUPERVISOR

JAN 16 1997

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____	T. Canyon _____
T. Salt _____	T. Strawn _____
B. Salt _____	T. Atoka _____
T. Yates _____ 2726'	T. Miss _____
T. 7 Rivers _____ 3104'	T. Devonian _____
T. Queen _____ 3712'	T. Silurian _____
T. Grayburg _____ 4074'	T. Montoya _____
T. San Andres _____ 4582'	T. Simpson _____
T. Glorieta _____	T. McKee _____
T. Paddock _____	T. Ellenburger _____
T. Blinebry _____	T. Gr. Wash _____
T. Tubb _____	T. Delaware Sand _____
T. Drinkard _____	T. Bone Springs _____
 T. Abo _____	 T. _____
T. Wolfcamp _____	T. _____
T. Penn _____	T. _____
T. Cisco (Bough C) _____	T. _____

Northwestern New Mexico

T. Ojo Alamo _____	T. Penn. "B" _____
T. Kirtland-Fruitland _____	T. Penn. "C" _____
T. Pictured Cliffs _____	T. Penn. "D" _____
T. Cliff House _____	T. Leadville _____
T. Menefee _____	T. Madison _____
T. Point Lookout _____	T. Elbert _____
T. Mancos _____	T. McCracken _____
T. Gallup _____	T. Ignacio Otzte _____
Base Greenhorn _____	T. Granite _____
T. Dakota _____	T. _____
T. Morrison _____	T. _____
T. Todilto _____	T. _____
T. Entrada _____	T. _____
 T. Wingate _____	 T. _____
T. Chinle _____	T. _____
T. Permian _____	T. _____
T. Penn "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____	No. 3, from _____ to _____
No. 2, from _____ to _____	No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet	_____ feet
No. 2, from _____ to _____ feet	_____ feet
No. 3, from _____ to _____ feet	_____ feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology