

ATTACHMENT

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT
OIL CONSERVATION DIVISION

FORM C-105

SEELY OIL COMPANY
CENTRAL EK QUEEN UNIT WELL #13
SE/4 SW/4 SECTION 7, 18S, 34E
LEA COUNTY, NEW MEXICO

23. Casing Record:

8-5/8" OD, 24# surface casing cemented with 580 sxs 65/35 Class C w/1/4# of Celoflake/sx followed by 250 sxs Class C w/1/4# of Celoflake/sx & 2% CaCl. Plug down 10:30 a.m. 11/9/97.

4-1/2" OD, 11.6# casing cemented w/225 sxs Halliburton Lite w/9# salt/sx followed by 225 sxs Premium Pozmix w/6# salt/sx & 1% CFR-3. Plug down @ 4:42 a.m. 11/15/97. Top of cement @ 3020' RKB.

27 Acid, Shot, Fracture, Cement, Squeeze, Etc.

11/26/97	4407-4420'	Acidized w/1500 gals. 15% MCA utilizing ball sealers to ball out.
12/6/97	4407-4420'	Fracture treated w/10,000 gals. gelled wtr. w/15,500# 16/30 sand.