

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	
T. Salt	
B. Salt	2496'
T. Yates	2678'
T. 7 Rivers	2982'
T. Queen	3634'
T. Grayburg	3988'
T. San Andres	4345'
T. Glorieta	
T. Paddock	
T. Blinebry	
T. Tubb	
T. Drinkard	
T. Abo	
T. Wolfcamp	
T. Penn	
T. Cisco (Bough C)	

T. Canyon
T. Strawn
T. Atoka
T. Miss
T. Devonian
T. Silurian
T. Montoya
T. Simpson
T. McKee
T. Ellenburger
T. Gr. Wash
T. Delaware Sand
T. Bone Springs
T.
T.
T.
T.

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Pictured Cliffs _____
T. Cliff House _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Gallup _____
Base Greenhorn _____
T. Dakota _____
T. Morrison _____
T. Todilto _____
T. Entrada _____
T. Wingate _____
T. Chinle _____
T. Permian _____
T. Penn "A" _____

T. Penn. "B" _____
T. Penn. "C" _____
T. Penn. "D" _____
T. Leadville _____
T. Madison _____
T. Elbert _____
T. McCracken _____
T. Ignacio Otzte _____
T. Granite _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from to
No. 2, from to
No. 3, from to
No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from..... tofeet.....
 No. 2, from..... tofeet.....
 No. 3, from..... tofeet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology
0'	450'	450'	Caliche & Sand
450'	1360'	910'	Redbed
1360'	1510'	150'	Anhydrite
1510'	2496'	986'	Salt
2496'	4550'	2054'	Dolomite, Sand & Anhydrite